There are two ways to resume execution of an application that is stopped in the debugger:

continue [n]: resumes program execution at the address where your script last stopped; any breakpoints set at that address are bypassed. The optional argument n allows you to specify a line number to set a one-time breakpoint which is deleted when that breakpoint is reached.
finish [n]: execute until the selected stack frame returns. If no frame number is given, the application will run until the currently selected frame returns. The currently selected frame starts out the most-recent frame or 0 if no frame positioning (e.g up, down or frame) has been performed. If a frame number is given it will run until the specified frame returns.

3.10 Editing

Two commands allow you to open code from the debugger into an editor:
edit [file:n]: edit file named file using the editor specified by the EDITOR environment variable.

A specific line n can also be given. 3.11 Quitting

To exit the debugger, use the quit command (abbreviated to q). Or, type q! to bypass the Really quit? (y/n) prompt and exit unconditionally.

A simple quit tries to terminate all threads in effect. Therefore your server will be stopped and you will have to start it again.

3.12 Settings

byebug has a few available options to tweak its behavior:

```
(byebug) help set
  set <setting> <value>
  Modifies byebug settings
  Boolean values take "on", "off", "true", "false", "1" or "0". If you
  don't specify a value, the boolean setting will be enabled.
Conversely,
  you can use "set no<setting>" to disable them.
  You can see these environment settings with the "show" command.
```