4.3.2.10 :source_type

The :source_type option specifies the source association type for a has_many :throughassociation that proceeds through a polymorphic association.

4.3.2.11 :through

The :through option specifies a join model through which to perform the query. has_many :throughassociations provide a way to implement many-to-many relationships, as discussed earlier in this guide.

4.3.2.12 :validate

If you set the :validate option to false, then associated objects will not be validated whenever you save this object. By default, this is true: associated objects will be validated when this object is saved.

4.3.3 Scopes for has_many

There may be times when you wish to customize the query used by has_many. Such customizations can be achieved via a scope block. For example:

```
class Customer < ActiveRecord::Base
  has_many :orders, -> { where processed: true }
end
```

You can use any of the standard querying methods inside the scope block. The following ones are discussed below:

- where
- extending
- group
- includes
- limit
- offset
- order
- readonly
- select
- uniq

4.3.3.1 where

The where method lets you specify the conditions that the associated object must meet.

```
class Customer < ActiveRecord::Base
  has_many :confirmed_orders, -> { where "confirmed = 1" },
    class_name: "Order"
end
```

You can also set conditions via a hash:

```
class Customer < ActiveRecord::Base
  has_many :confirmed_orders, -> { where confirmed: true },
                              class_name: "Order"
end
```

If you use a hash-style where option, then record creation via this association will be automatically scoped using the hash. In this case,
using @customer.confirmed_orders.create or @customer.confirmed_orders.build will create orders where the confirmed column has the value true.

4.3.3.2 extending

The extending method specifies a named module to extend the association proxy. Association extensions are discussed in detail later in this guide.

4.3.3.3 group

The group method supplies an attribute name to group the result set by, using a GROUP BY clause in the finder SQL.