```
class Parts < ActiveRecord::Base
  has_and_belongs_to_many :assemblies,
    -> { where factory: 'Seattle' }
end
```

If you use a hash-style `where`, then record creation via this association will be automatically scoped using the hash. In this case, using `@parts.assemblies.create` or `@parts.assemblies.build` will create orders where the `factory` column has the value "Seattle".

4.4.3.2 `extending`

The `extending` method specifies a named module to extend the association proxy. Association extensions are discussed in detail later in this guide.

4.4.3.3 `group`

The `group` method supplies an attribute name to group the result set by, using a `GROUP BY` clause in the finder SQL.

```
class Parts < ActiveRecord::Base
  has_and_belongs_to_many :assemblies, -> { group "factory" }
end
```

4.4.3.4 `includes`

You can use the `includes` method to specify second-order associations that should be eager-loaded when this association is used.

4.4.3.5 `limit`

The `limit` method lets you restrict the total number of objects that will be fetched through an association.

```
class Parts < ActiveRecord::Base
  has_and_belongs_to_many :assemblies,
    -> { order("created_at DESC").limit(50) }
end
```

4.4.3.6 `offset`

The `offset` method lets you specify the starting offset for fetching objects via an association. For example, if you set `offset(11)`, it will skip the first 11 records.

4.4.3.7 `order`

The `order` method dictates the order in which associated objects will be received (in the syntax used by an SQL `ORDER BY` clause).

```
class Parts < ActiveRecord::Base
  has_and_belongs_to_many :assemblies,
    -> { order "assembly_name ASC" }
end
```

4.4.3.8 `readonly`

If you use the `readonly` method, then the associated objects will be read-only when retrieved via the association.

4.4.3.9 `select`

The `select` method lets you override the SQL `SELECT` clause that is used to retrieve data about the associated objects. By default, Rails retrieves all columns.

4.4.3.10 `uniq`

Use the `uniq` method to remove duplicates from the collection.

4.4.4 When are Objects Saved?

When you assign an object to a `has_and_belongs_to_many` association, that object is automatically saved (in order to update the join table). If you assign multiple objects in one statement, then they are all saved.

If any of these saves fails due to validation errors, then the assignment statement returns `false` and the assignment itself is cancelled.