2.2.8 Rendering HTML

You can send an HTML string back to the browser by using the `:html` option to `render`:

```
render html: "<strong>Not Found</strong>".html_safe
```

This is useful when you're rendering a small snippet of HTML code. However, you might want to consider moving it to a template file if the markup is complex.

This option will escape HTML entities if the string is not HTML safe.

2.2.9 Rendering JSON

JSON is a JavaScript data format used by many Ajax libraries. Rails has built-in support for converting objects to JSON and rendering that JSON back to the browser:

```
render json: @product
```

You don't need to call `to_json` on the object that you want to render. If you use the `:json`option, `render` will automatically call `to_json` for you.

2.2.10 Rendering XML

Rails also has built-in support for converting objects to XML and rendering that XML back to the caller:

```
render xml: @product
```

You don't need to call `to_xml` on the object that you want to render. If you use the `:xml`option, `render` will automatically call `to_xml` for you.

2.2.11 Rendering Vanilla JavaScript

Rails can render vanilla JavaScript:

```
render js: "alert('Hello Rails');"
```

This will send the supplied string to the browser with a MIME type of `text/javascript`.

2.2.12 Rendering raw body

You can send a raw content back to the browser, without setting any content type, by using the `:body`option to `render`:

```
render body: "raw"
```

This option should be used only if you don't care about the content type of the response. Using `:plain` or `:html` might be more appropriate in most of the time.

Unless overridden, your response returned from this render option will be `text/html`, as that is the default content type of Action Dispatch response.

2.2.13 Options for `render`

Calls to the `render` method generally accept five options:

- `:content_type`
- `:layout`
- `:location`
- `:status`
- `:formats`

2.2.13.1 The `:content_type` Option

By default, Rails will serve the results of a rendering operation with the MIME content-type of `text/html` (or `application/json` if you use the `:json` option, or `application/xml` for