the `:xml`option.). There are times when you might like to change this, and you can do so by setting the `:content_type` option:

```
render file: filename, content_type: "application/rss"
```

2.2.13.2 The `:layout` Option

With most of the options to `render`, the rendered content is displayed as part of the current layout. You'll learn more about layouts and how to use them later in this guide.

You can use the `:layout` option to tell Rails to use a specific file as the layout for the current action:

```
render layout: "special_layout"
```

You can also tell Rails to render with no layout at all:

```
render layout: false
```

2.2.13.3 The `:location` Option

You can use the `:location` option to set the HTTP `Location` header:

```
render xml: photo, location: photo_url(photo)
```

2.2.13.4 The `:status` Option

Rails will automatically generate a response with the correct HTTP status code (in most cases, this is `200 OK`). You can use the `:status` option to change this:

```
render status: 500
render status: :forbidden
```

Rails understands both numeric status codes and the corresponding symbols shown below.

Response Class	HTTP Status Code	Symbol
Informational	100	:continue
	101	:switching_protocols
	102	:processing
Success	200	:ok
	201	:created
	202	:accepted
	203	:non_authoritative_information
	204	:no_content
	205	:reset_content
	206	:partial_content
	207	:multi_status
	208	:already_reported
	226	:im_used
Redirection	300	:multiple_choices