You can specify a full path relative to the document root, or a URL, if you prefer. For example, to link to a JavaScript file that is inside a directory called `javascripts` inside of one of `app/assets`, `lib/assets` or `vendor/assets`, you would do this:

```
<%= javascript_include_tag "main" %>
```

Rails will then output a `script` tag such as this:

```
<script src='/assets/main.js'></script>
```

The request to this asset is then served by the Sprockets gem.

To include multiple files such as `app/assets/javascripts/main.js` and `app/assets/javascripts/columns.js` at the same time:

```
<%= javascript_include_tag "main", "columns" %>
```

To include `app/assets/javascripts/main.js` and `app/assets/javascripts/photos/columns.js`:

```
<%= javascript_include_tag "main", "/photos/columns" %>
```

To include `http://example.com/main.js`:

```
<%= javascript_include_tag "http://example.com/main.js" %>
```

3.1.3 Linking to CSS Files with the `stylesheet_link_tag`

The `stylesheet_link_tag` helper returns an HTML `<link>` tag for each source provided.

If you are using Rails with the "Asset Pipeline" enabled, this helper will generate a link to `/assets/stylesheets/`. This link is then processed by the Sprockets gem. A stylesheet file can be stored in one of three locations: `app/assets`, `lib/assets` or `vendor/assets`.

You can specify a full path relative to the document root, or a URL. For example, to link to a stylesheet file that is inside a directory called `stylesheets` inside of one of `app/assets`, `lib/assetsor` `vendor/assets`, you would do this:

```
<%= stylesheet_link_tag "main" %>
```

To include `app/assets/stylesheets/main.css` and `app/assets/stylesheets/columns.css`:

```
<%= stylesheet_link_tag "main", "columns" %>
```

To include `app/assets/stylesheets/main.css` and `app/assets/stylesheets/photos/columns.css`:

```
<%= stylesheet_link_tag "main", "photos/columns" %>
```

To include `http://example.com/main.css`:

```
<%= stylesheet_link_tag "http://example.com/main.css" %>
```

By default, the `stylesheet_link_tag` creates links with `media="screen" rel="stylesheet"`. You can override any of these defaults by specifying an appropriate option (`:media`, `:rel`):

```
<%= stylesheet_link_tag "main_print", media: "print" %>
```

3.1.4 Linking to Images with the `image_tag`

The `image_tag` helper builds an HTML `<img />` tag to the specified file. By default, files are loaded from `public/images`.

Note that you must specify the extension of the image.

```
<%= image_tag "header.png" %>
```

You can supply a path to the image if you like:

```
<%= image_tag "icons/delete.gif" %>
```

You can supply a hash of additional HTML options:

```
<%= image_tag "icons/delete.gif", {height: 45} %>
```

You can supply alternate text for the image which will be used if the user has images turned off in their browser. If you do not specify an alt text explicitly, it defaults to the file name of the file, capitalized and with no extension. For example, these two image tags would return the same code:

```
<%= image_tag "home.gif" %>
```