```
<%= image_tag "home.gif", alt: "Home" %>
```
You can also specify a special size tag, in the format "{width}x{height}":

```
<%= image_tag "home.gif", size: "50x20" %>
```
In addition to the above special tags, you can supply a final hash of standard HTML options, such as `:class`, `:id` or `:name`:
```
<%= image_tag "home.gif", alt: "Go Home",
                          id: "HomeImage",
                          class: "nav_bar" %>
```

3.1.5 Linking to Videos with the `video_tag`

The `video_tag` helper builds an HTML 5 `<video>` tag to the specified file. By default, files are loaded from `public/videos`.
```
<%= video_tag "movie.ogg" %>
```
Produces

```
<video src="/videos/movie.ogg" />
```
Like an `image_tag` you can supply a path, either absolute, or relative to the `public/videos`directory. Additionally you can specify the `size: "#{width}x#{height}"` option just like an `image_tag`. Video tags can also have any of the HTML options specified at the end (`id`, `class` et al).
The video tag also supports all of the `<video>` HTML options through the HTML options hash, including:

- `poster: "image_name.png"`, provides an image to put in place of the video before it starts playing.
- `autoplay: true`, starts playing the video on page load.
- `loop: true`, loops the video once it gets to the end.
- `controls: true`, provides browser supplied controls for the user to interact with the video.
- `autobuffer: true`, the video will pre load the file for the user on page load.

You can also specify multiple videos to play by passing an array of videos to the `video_tag`:
```
<%= video_tag ["trailer.ogg", "movie.ogg"] %>
```
This will produce:

```
<video>
  <source src="/videos/trailer.ogg">
  <source src="/videos/movie.ogg">
</video>
```

3.1.6 Linking to Audio Files with the `audio_tag`

The `audio_tag` helper builds an HTML 5 `<audio>` tag to the specified file. By default, files are loaded from `public/audios`.
```
<%= audio_tag "music.mp3" %>
```
You can supply a path to the audio file if you like:

```
<%= audio_tag "music/first_song.mp3" %>
```
You can also supply a hash of additional options, such as `:id`, `:class` etc.
Like the `video_tag`, the `audio_tag` has special options:

- `autoplay: true`, starts playing the audio on page load
- `controls: true`, provides browser supplied controls for the user to interact with the audio.
- `autobuffer: true`, the audio will pre load the file for the user on page load.