```
        'street' => '31 Spooner Street'
      }
    }
  }
}
```

The keys of the `:addresses_attributes` hash are unimportant, they need merely be different for each address.

If the associated object is already saved, `fields_for` autogenerates a hidden input with the `id` of the saved record. You can disable this by passing `include_id: false` to `fields_for`. You may wish to do this if the autogenerated input is placed in a location where an input tag is not valid HTML or when using an ORM where children do not have an `id`.

9.3 The Controller

As usual you need to whitelist the parameters in the controller before you pass them to the model:

```
def create
  @person = Person.new(person_params)
  # ...
end

private
  def person_params
    params.require(:person).permit(:name, addresses_attributes: [:id,
:kind, :street])
  end
```

9.4 Removing Objects

You can allow users to delete associated objects by passing `allow_destroy: true` to `accepts_nested_attributes_for`

```
class Person < ActiveRecord::Base
  has_many :addresses
  accepts_nested_attributes_for :addresses, allow_destroy: true
end
```

If the hash of attributes for an object contains the key `_destroy` with a value of `1` or `true` then the object will be destroyed. This form allows users to remove addresses:

```
<%= form_for @person do |f| %>
  Addresses:
  <ul>
    <%= f.fields_for :addresses do |addresses_form| %>
      <li>
        <%= addresses_form.check_box :_destroy%>
        <%= addresses_form.label :kind %>
        <%= addresses_form.text_field :kind %>
        ...
      </li>
    <% end %>
  </ul>
<% end %>
```

Don't forget to update the whitelisted params in your controller to also include the `_destroy` field:

```
def person_params
  params.require(:person).
    permit(:name, addresses_attributes: [:id, :kind, :street,
:_destroy])
end
```