`resources :photos`
Rails would dispatch that request to the `destroy` method on the `photos` controller with `{ id: '17' }` in `params`.

2.2 CRUD, Verbs, and Actions

In Rails, a resourceful route provides a mapping between HTTP verbs and URLs to controller actions. By convention, each action also maps to particular CRUD operations in a database. A single entry in the routing file, such as:

`resources :photos`
creates seven different routes in your application, all mapping to the `Photos` controller:

HTTP Verb	Path	Controller#Action	Used for
GET	/photos	photos#index	display a list of all photos
GET	/photos/new	photos#new	return an HTML form for creating a new photo
POST	/photos	photos#create	create a new photo
GET	/photos/:id	photos#show	display a specific photo
GET	/photos/:id/edit	photos#edit	return an HTML form for editing a photo
PATCH/PUT	/photos/:id	photos#update	update a specific photo
DELETE	/photos/:id	photos#destroy	delete a specific photo

Because the router uses the HTTP verb and URL to match inbound requests, four URLs map to seven different actions.

Rails routes are matched in the order they are specified, so if you have a `resources :photos` above a `get 'photos/poll'` the `show` action's route for the `resources` line will be matched before the `get` line. To fix this, move the `get` line **above** the `resources` line so that it is matched first.

2.3 Path and URL Helpers

Creating a resourceful route will also expose a number of helpers to the controllers in your application. In the case of `resources :photos`:

- `photos_path` returns `/photos`
- `new_photo_path` returns `/photos/new`
- `edit_photo_path(:id)` returns `/photos/:id/edit` (for instance, `edit_photo_path(10)`returns `/photos/10/edit`)
- `photo_path(:id)` returns `/photos/:id` (for instance, `photo_path(10)` returns `/photos/10`)

Each of these helpers has a corresponding `_url` helper (such as `photos_url`) which returns the same path prefixed with the current host, port and path prefix.

2.4 Defining Multiple Resources at the Same Time

If you need to create routes for more than one resource, you can save a bit of typing by defining them all with a single call to `resources`: