```
resources :photos, :books, :videos
```
This works exactly the same as:

```
resources :photos
resources :books
resources :videos
```

2.5 Singular Resources

Sometimes, you have a resource that clients always look up without referencing an ID. For example, you would like `/profile` to always show the profile of the currently logged in user. In this case, you can use a singular resource to map `/profile` (rather than `/profile/:id`) to the `show` action:

```
get 'profile', to: 'users#show'
```
Passing a `String` to `get` will expect a `controller#action` format, while passing a `Symbol` will map directly to an action:

```
get 'profile', to: :show
```
This resourceful route:

```
resource :geocoder
```
creates six different routes in your application, all mapping to the `Geocoders` controller:

HTTP Verb	Path	Controller#Action	Used for
GET	/geocoder/new	geocoders#new	return an HTML form for creating the geocoder
POST	/geocoder	geocoders#create	create the new geocoder
GET	/geocoder	geocoders#show	display the one and only geocoder resource
GET	/geocoder/edit	geocoders#edit	return an HTML form for editing the geocoder
PATCH/PUT	/geocoder	geocoders#update	update the one and only geocoder resource
DELETE	/geocoder	geocoders#destroy	delete the geocoder resource

Because you might want to use the same controller for a singular route (`/account`) and a plural route (`/accounts/45`), singular resources map to plural controllers. So that, for example, `resource :photo` and `resources :photos` creates both singular and plural routes that map to the same controller (`PhotosController`).

A singular resourceful route generates these helpers:

- `new_geocoder_path` returns `/geocoder/new`
- `edit_geocoder_path` returns `/geocoder/edit`
- `geocoder_path` returns `/geocoder`

As with plural resources, the same helpers ending in `_url` will also include the host, port and path prefix.
A long-standing bug prevents `form_for` from working automatically with singular resources. As a workaround, specify the URL for the form directly, like so:

```
form_for @geocoder, url: geocoder_path do |f|
```