```
  <p>
    <%= f.label :title %><br>
    <%= f.text_field :title %>
  </p>

  <p>
    <%= f.label :text %><br>
    <%= f.text_area :text %>
  </p>

  <p>
    <%= f.submit %>
  </p>

<% end %>
```

Everything except for the `form_for` declaration remained the same. The reason we can use this shorter, simpler `form_for` declaration to stand in for either of the other forms is that `@article` is a *resource* corresponding to a full set of RESTful routes, and Rails is able to infer which URI and method to use. For more information about this use of `form_for`, see Resource-oriented style.

Now, let's update the `app/views/articles/new.html.erb` view to use this new partial, rewriting it completely:

```
<h1>New article</h1>

<%= render 'form' %>

<%= link_to 'Back', articles_path %>
```

Then do the same for the `app/views/articles/edit.html.erb` view:

```
<h1>Edit article</h1>

<%= render 'form' %>

<%= link_to 'Back', articles_path %>
```

5.13 Deleting Articles

We're now ready to cover the "D" part of CRUD, deleting articles from the database. Following the REST convention, the route for deleting articles as per output of `rake routes` is:

```
DELETE /articles/:id(.:format)      articles#destroy
```

The `delete` routing method should be used for routes that destroy resources. If this was left as a typical `get` route, it could be possible for people to craft malicious URLs like this:

```
<a href='http://example.com/articles/1/destroy'>look at this cat!</a>
```

We use the `delete` method for destroying resources, and this route is mapped to the `destroy` action inside `app/controllers/articles_controller.rb`, which doesn't exist yet. The `destroy` method is generally the last CRUD action in the controller, and like the other public CRUD actions, it must be placed before any `private` or `protected` methods. Let's add it:

```
def destroy
  @article = Article.find(params[:id])
  @article.destroy

  redirect_to articles_path
end
```

The complete `ArticlesController` in the `app/controllers/articles_controller.rb` file should now look like this:

```
class ArticlesController < ApplicationController
  def index
    @articles = Article.all
  end
```