```
  end
end
```

Request constraints work by calling a method on the Request object with the same name as the hash key and then compare the return value with the hash value. Therefore, constraint values should match the corresponding Request object method return type. For example: `constraints: { subdomain: 'api' }` will match an `api` subdomain as expected, however using a symbol `constraints: { subdomain: :api }` will not, because `request.subdomain` returns `'api'` as a String.

3.10 Advanced Constraints

If you have a more advanced constraint, you can provide an object that responds to `matches?` that Rails should use. Let's say you wanted to route all users on a blacklist to the `BlacklistController`. You could do:

```
class BlacklistConstraint
  def initialize
    @ips = Blacklist.retrieve_ips
  end

  def matches?(request)
    @ips.include?(request.remote_ip)
  end
end

Rails.application.routes.draw do
  get '*path', to: 'blacklist#index',
    constraints: BlacklistConstraint.new
end
```

You can also specify constraints as a lambda:

```
Rails.application.routes.draw do
  get '*path', to: 'blacklist#index',
    constraints: lambda { |request|
Blacklist.retrieve_ips.include?(request.remote_ip) }
end
```

Both the `matches?` method and the lambda gets the `request` object as an argument.

3.11 Route Globbing and Wildcard Segments

Route globbing is a way to specify that a particular parameter should be matched to all the remaining parts of a route. For example:

```
get 'photos/*other', to: 'photos#unknown'
```

This route would match `photos/12` or `/photos/long/path/to/12`,
setting `params[:other]` to `"12"`or `"long/path/to/12"`. The fragments prefixed with a star are called "wildcard segments".
Wildcard segments can occur anywhere in a route. For example:

```
get 'books/*section/:title', to: 'books#show'
```

would match `books/some/section/last-words-a-memoir` with `params[:section]` equals `'some/section'`, and `params[:title]` equals `'last-words-a-memoir'`.
Technically, a route can have even more than one wildcard segment. The matcher assigns segments to parameters in an intuitive way. For example: