```
  root to: "admin#index"
end

root to: "home#index"
```

3.15 Unicode character routes

You can specify unicode character routes directly. For example:

```
get 'こんにちは', to: 'welcome#index'
```

4 Customizing Resourceful Routes

While the default routes and helpers generated by `resources :articles` will usually serve you well, you may want to customize them in some way. Rails allows you to customize virtually any generic part of the resourceful helpers.

4.1 Specifying a Controller to Use

The `:controller` option lets you explicitly specify a controller to use for the resource. For example:
`resources :photos, controller: 'images'`
will recognize incoming paths beginning with `/photos` but route to the `Images` controller:

HTTP Verb	Path	Controller#Action	Named Helper
GET	/photos	images#index	photos_path
GET	/photos/new	images#new	new_photo_path
POST	/photos	images#create	photos_path
GET	/photos/:id	images#show	photo_path(:id)
GET	/photos/:id/edit	images#edit	edit_photo_path(:id)
PATCH/PUT	/photos/:id	images#update	photo_path(:id)
DELETE	/photos/:id	images#destroy	photo_path(:id)

Use `photos_path`, `new_photo_path`, etc. to generate paths for this resource.

For namespaced controllers you can use the directory notation. For example:

```
resources :user_permissions, controller: 'admin/user_permissions'
```

This will route to the `Admin::UserPermissions` controller.
Only the directory notation is supported. Specifying the controller with Ruby constant notation (eg. `controller: 'Admin::UserPermissions'`) can lead to routing problems and results in a warning.

4.2 Specifying Constraints

You can use the `:constraints` option to specify a required format on the implicit `id`. For example:
`resources :photos, constraints: { id: /[A-Z][A-Z][0-9]+/ }`