HTTP Verb	Path	Controller#Action	Named Helper
GET	/kategorien/neu	categories#new	new_category_path
POST	/kategorien	categories#create	categories_path
GET	/kategorien/:id	categories#show	category_path(:id)
GET	/kategorien/:id/bearbeiten	categories#edit	edit_category_path(:id)
PATCH/PUT	/kategorien/:id	categories#update	category_path(:id)
DELETE	/kategorien/:id	categories#destroy	category_path(:id)

4.8 Overriding the Singular Form

If you want to define the singular form of a resource, you should add additional rules to the `Inflector`:

```
ActiveSupport::Inflector.inflections do |inflect|
  inflect.irregular 'tooth', 'teeth'
end
```

4.9 Using `:as` in Nested Resources

The `:as` option overrides the automatically-generated name for the resource in nested route helpers. For example:

```
resources :magazines do
  resources :ads, as: 'periodical_ads'
end
```

This will create routing helpers such as `magazine_periodical_ads_url` and `edit_magazine_periodical_ad_path`.

4.10 Overriding Named Route Parameters

The `:param` option overrides the default resource identifier `:id` (name of the dynamic segment used to generate the routes). You can access that segment from your controller using `params[<:param>]`.

```
resources :videos, param: :identifier
     videos GET  /videos(.:format)                  videos#index
            POST /videos(.:format)                  videos#create
 new_videos GET  /videos/new(.:format)              videos#new
edit_videos GET  /videos/:identifier/edit(.:format) videos#edit
Video.find_by(identifier: params[:identifier])
```

5 Inspecting and Testing Routes

Rails offers facilities for inspecting and testing your routes.

5.1 Listing Existing Routes

To get a complete list of the available routes in your application, visit `http://localhost:3000/rails/info/routes` in your browser while your server is running in the**development** environment. You can also execute the `rake routes` command in your terminal to produce the same output.