5.11.5 titleize

The method titleize capitalizes the words in the receiver:

```
"alice in wonderland".titleize # => "Alice In Wonderland"
"fermat's enigma".titleize     # => "Fermat's Enigma"
```

titleize is aliased to titlecase.

Defined in active_support/core_ext/string/inflections.rb.

5.11.6 dasherize

The method dasherize replaces the underscores in the receiver with dashes:

```
"name".dasherize         # => "name"
"contact_data".dasherize # => "contact-data"
```

The XML serializer of models uses this method to dasherize node names:

```
# active_model/serializers/xml.rb
def reformat_name(name)
  name = name.camelize if camelize?
  dasherize? ? name.dasherize : name
end
```

Defined in active_support/core_ext/string/inflections.rb.

5.11.7 demodulize

Given a string with a qualified constant name, demodulize returns the very constant name, that is, the rightmost part of it:

```
"Product".demodulize                        # => "Product"
"Backoffice::UsersController".demodulize    # => "UsersController"
"Admin::Hotel::ReservationUtils".demodulize # => "ReservationUtils"
"::Inflections".demodulize                  # => "Inflections"
"".demodulize                               # => ""
```

Active Record for example uses this method to compute the name of a counter cache column:

```
# active_record/reflection.rb
def counter_cache_column
  if options[:counter_cache] == true
    "#{active_record.name.demodulize.underscore.pluralize}_count"
  elsif options[:counter_cache]
    options[:counter_cache]
  end
end
```

Defined in active_support/core_ext/string/inflections.rb.

5.11.8 deconstantize

Given a string with a qualified constant reference expression, deconstantize removes the rightmost segment, generally leaving the name of the constant's container:

```
"Product".deconstantize                        # => ""
"Backoffice::UsersController".deconstantize    # => "Backoffice"
"Admin::Hotel::ReservationUtils".deconstantize # => "Admin::Hotel"
```

Active Support for example uses this method in Module#qualified_const_set:

```
def qualified_const_set(path, value)
  QualifiedConstUtils.raise_if_absolute(path)

  const_name = path.demodulize
  mod_name = path.deconstantize
  mod = mod_name.empty? ? self : qualified_const_get(mod_name)
  mod.const_set(const_name, value)
end
```

Defined in active_support/core_ext/string/inflections.rb.

5.11.9 parameterize

The method parameterize normalizes its receiver in a way that can be used in pretty URLs.