The method `to_sentence` turns an array into a string containing a sentence that enumerates its items:

```
%w().to_sentence                # => ""
%w(Earth).to_sentence           # => "Earth"
%w(Earth Wind).to_sentence      # => "Earth and Wind"
%w(Earth Wind Fire).to_sentence # => "Earth, Wind, and Fire"
```

This method accepts three options:

- `:two_words_connector`: What is used for arrays of length 2. Default is " and ".
- `:words_connector`: What is used to join the elements of arrays with 3 or more elements, except for the last two. Default is ", ".
- `:last_word_connector`: What is used to join the last items of an array with 3 or more elements. Default is ", and ".

The defaults for these options can be localized, their keys are:

Option	I18n key
`:two_words_connector`	`support.array.two_words_connector`
`:words_connector`	`support.array.words_connector`
`:last_word_connector`	`support.array.last_word_connector`

Defined in `active_support/core_ext/array/conversions.rb`.

10.4.2 `to_formatted_s`

The method `to_formatted_s` acts like `to_s` by default.

If the array contains items that respond to `id`, however, the symbol `:db` may be passed as argument.

That's typically used with collections of Active Record objects. Returned strings are:

```
[].to_formatted_s(:db)            # => "null"
[user].to_formatted_s(:db)        # => "8456"
invoice.lines.to_formatted_s(:db) # => "23,567,556,12"
```

Integers in the example above are supposed to come from the respective calls to `id`.

Defined in `active_support/core_ext/array/conversions.rb`.

10.4.3 `to_xml`

The method `to_xml` returns a string containing an XML representation of its receiver:

```
Contributor.limit(2).order(:rank).to_xml
# =>
# <?xml version="1.0" encoding="UTF-8"?>
# <contributors type="array">
#   <contributor>
#     <id type="integer">4356</id>
#     <name>Jeremy Kemper</name>
#     <rank type="integer">1</rank>
#     <url-id>jeremy-kemper</url-id>
#   </contributor>
#   <contributor>
#     <id type="integer">4404</id>
#     <name>David Heinemeier Hansson</name>
#     <rank type="integer">2</rank>
#     <url-id>david-heinemeier-hansson</url-id>
#   </contributor>
# </contributors>
```

To do so it sends `to_xml` to every item in turn, and collects the results under a root node. All items must respond to `to_xml`, an exception is raised otherwise.