"books#index" declaration in your routes.rb doesn't take locale into account. (And rightly so: there's only one "root" URL.)
You would probably need to map URLs like these:

```
# config/routes.rb
get '/:locale' => 'dashboard#index'
```

Do take special care about the **order of your routes**, so this route declaration does not "eat" other ones. (You may want to add it directly before the root :to declaration.)
Have a look at various gems which simplify working with routes: routing_filter, rails-translate-routes, route_translator.

2.6 Setting the Locale from the Client Supplied Information

In specific cases, it would make sense to set the locale from client-supplied information, i.e. not from the URL. This information may come for example from the users' preferred language (set in their browser), can be based on the users' geographical location inferred from their IP, or users can provide it simply by choosing the locale in your application interface and saving it to their profile. This approach is more suitable for web-based applications or services, not for websites - see the box about *sessions*, *cookies* and RESTful architecture above.

2.6.1 Using Accept-Language

One source of client supplied information would be an Accept-Language HTTP header. People mayset this in their browser or other clients (such as *curl*).
A trivial implementation of using an Accept-Language header would be:

```
def set_locale
  logger.debug "* Accept-Language:
#{request.env['HTTP_ACCEPT_LANGUAGE']}"
  I18n.locale = extract_locale_from_accept_language_header
  logger.debug "* Locale set to '#{I18n.locale}'"
end

private
  def extract_locale_from_accept_language_header
    request.env['HTTP_ACCEPT_LANGUAGE'].scan(/^[a-z]{2}/).first
  end
```

Of course, in a production environment you would need much more robust code, and could use a gem such as Iain Hecker's http_accept_language or even Rack middleware such as Ryan Tomayko'slocale.

2.6.2 Using GeoIP (or Similar) Database

Another way of choosing the locale from client information would be to use a database for mapping the client IP to the region, such as GeoIP Lite Country. The mechanics of the code would be very similar to the code above - you would need to query the database for the user's IP, and look up your preferred locale for the country/region/city returned.

2.6.3 User Profile

You can also provide users of your application with means to set (and possibly over-ride) the locale in your application interface, as well. Again, mechanics for this approach would be very similar to the code above - you'd probably let users choose a locale from a dropdown list and save it to their profile in the database. Then you'd set the locale to this value.

3 Internationalizing your Application