Rails implements a convenient way to look up the locale inside *views*. When you have the following dictionary:

```
es:
  books:
    index:
      title: "Título"
```

you can look up the `books.index.title` value **inside** `app/views/books/index.html.erb`template like this (note the dot):

```
<%= t '.title' %>
```

Automatic translation scoping by partial is only available from the `translate` view helper method.

"Lazy" lookup can also be used in controllers:

```
en:
  books:
    create:
      success: Book created!
```

This is useful for setting flash messages for instance:

```
class BooksController < ApplicationController
  def create
    # ...
    redirect_to books_url, notice: t('.success')
  end
end
```

4.2 Interpolation

In many cases you want to abstract your translations so that **variables can be interpolated into the translation**. For this reason the I18n API provides an interpolation feature.

All options besides `:default` and `:scope` that are passed to `#translate` will be interpolated to the translation:

```
I18n.backend.store_translations :en, thanks: 'Thanks %{name}!'
I18n.translate :thanks, name: 'Jeremy'
# => 'Thanks Jeremy!'
```

If a translation uses `:default` or `:scope` as an interpolation variable,
an `I18n::ReservedInterpolationKey` exception is raised. If a translation expects an interpolation variable, but this has not been passed to `#translate`,
an `I18n::MissingInterpolationArgument`exception is raised.

4.3 Pluralization

In English there are only one singular and one plural form for a given string, e.g. "1 message" and "2 messages". Other languages (Arabic, Japanese, Russian and many more) have different grammars that have additional or fewer plural forms. Thus, the I18n API provides a flexible pluralization feature.

The `:count` interpolation variable has a special role in that it both is interpolated to the translation and used to pick a pluralization from the translations according to the pluralization rules defined by CLDR:

```
I18n.backend.store_translations :en, inbox: {
  one: 'one message',
  other: '%{count} messages'
}
I18n.translate :inbox, count: 2
# => '2 messages'

I18n.translate :inbox, count: 1
# => 'one message'
```