```
<p>
  <strong>Commenter:</strong>
  <%= comment.commenter %>
</p>

<p>
  <strong>Comment:</strong>
  <%= comment.body %>
</p>
```

Then you can change `app/views/articles/show.html.erb` to look like the following:

```
<p>
  <strong>Title:</strong>
  <%= @article.title %>
</p>

<p>
  <strong>Text:</strong>
  <%= @article.text %>
</p>

<h2>Comments</h2>
<%= render @article.comments %>

<h2>Add a comment:</h2>
<%= form_for([@article, @article.comments.build]) do |f| %>
  <p>
    <%= f.label :commenter %><br>
    <%= f.text_field :commenter %>
  </p>
  <p>
    <%= f.label :body %><br>
    <%= f.text_area :body %>
  </p>
  <p>
    <%= f.submit %>
  </p>
<% end %>

<%= link_to 'Edit', edit_article_path(@article) %> |
<%= link_to 'Back', articles_path %>
```

This will now render the partial in `app/views/comments/_comment.html.erb` once for each comment that is in the `@article.comments` collection. As the `render` method iterates over the `@article.comments` collection, it assigns each comment to a local variable named the same as the partial, in this case `comment` which is then available in the partial for us to show.

7.2 Rendering a Partial Form

Let us also move that new comment section out to its own partial. Again, you create a file `app/views/comments/_form.html.erb` containing:

```
<%= form_for([@article, @article.comments.build]) do |f| %>
  <p>
    <%= f.label :commenter %><br>
    <%= f.text_field :commenter %>
  </p>
  <p>
    <%= f.label :body %><br>
    <%= f.text_area :body %>
  </p>
  <p>
    <%= f.submit %>
  </p>
<% end %>
```