the `Mail::Message` object you can access it with the `message` method on the `ActionMailer::MessageDelivery` object.

2.2 Auto encoding header values

Action Mailer handles the auto encoding of multibyte characters inside of headers and bodies.

For more complex examples such as defining alternate character sets or self-encoding text first, please refer to the Mail library.

2.3 Complete List of Action Mailer Methods

There are just three methods that you need to send pretty much any email message:

- `headers` - Specifies any header on the email you want. You can pass a hash of header field names and value pairs, or you can call `headers[:field_name] = 'value'`.
- `attachments` - Allows you to add attachments to your email. For example, `attachments['file-name.jpg'] = File.read('file-name.jpg')`.
- `mail` - Sends the actual email itself. You can pass in headers as a hash to the mail method as a parameter, mail will then create an email, either plain text, or multipart, depending on what email templates you have defined.

2.3.1 Adding Attachments

Action Mailer makes it very easy to add attachments.

- Pass the file name and content and Action Mailer and the Mail gem will automatically guess the mime_type, set the encoding and create the attachment.

```
attachments['filename.jpg'] =
File.read('/path/to/filename.jpg')
```

When the `mail` method will be triggered, it will send a multipart email with an attachment, properly nested with the top level being `multipart/mixed` and the first part being a `multipart/alternative`containing the plain text and HTML email messages.
Mail will automatically Base64 encode an attachment. If you want something different, encode your content and pass in the encoded content and encoding in a `Hash` to the `attachments` method.

- Pass the file name and specify headers and content and Action Mailer and Mail will use the settings you pass in.

```
encoded_content =
SpecialEncode(File.read('/path/to/filename.jpg'))
attachments['filename.jpg'] = {
  mime_type: 'application/x-gzip',
  encoding: 'SpecialEncoding',
  content: encoded_content
}
```

If you specify an encoding, Mail will assume that your content is already encoded and not try to Base64 encode it.

2.3.2 Making Inline Attachments

Action Mailer 3.0 makes inline attachments, which involved a lot of hacking in pre 3.0 versions, much simpler and trivial as they should be.