- First, to tell Mail to turn an attachment into an inline attachment, you just call `#inline` on the attachments method within your Mailer:
```
def welcome
  attachments.inline['image.jpg'] =
File.read('/path/to/image.jpg')
end
```
- Then in your view, you can just reference `attachments` as a hash and specify which attachment you want to show, calling `url` on it and then passing the result into the `image_tag` method:
```
<p>Hello there, this is our image</p>

<%= image_tag attachments['image.jpg'].url %>
```
- As this is a standard call to `image_tag` you can pass in an options hash after the attachment URL as you could for any other image:
```
<p>Hello there, this is our image</p>

<%= image_tag attachments['image.jpg'].url, alt: 'My Photo',
class: 'photos' %>
```

2.3.3 Sending Email To Multiple Recipients

It is possible to send email to one or more recipients in one email (e.g., informing all admins of a new signup) by setting the list of emails to the `:to` key. The list of emails can be an array of email addresses or a single string with the addresses separated by commas.

```
class AdminMailer < ActionMailer::Base
  default to: Proc.new { Admin.pluck(:email) },
          from: 'notification@example.com'

  def new_registration(user)
    @user = user
    mail(subject: "New User Signup: #{@user.email}")
  end
end
```

The same format can be used to set carbon copy (Cc:) and blind carbon copy (Bcc:) recipients, by using the `:cc` and `:bcc` keys respectively.

2.3.4 Sending Email With Name

Sometimes you wish to show the name of the person instead of just their email address when they receive the email. The trick to doing that is to format the email address in the format `"Full Name <email>"`.

```
def welcome_email(user)
  @user = user
  email_with_name = %("#{@user.name}" <#{@user.email}>)
  mail(to: email_with_name, subject: 'Welcome to My Awesome Site')
end
```

2.4 Mailer Views

Mailer views are located in the `app/views/name_of_mailer_class` directory. The specific mailer view is known to the class because its name is the same as the mailer method. In our example from above, our mailer view for the `welcome_email` method will be

in `app/views/user_mailer/welcome_email.html.erb` for the HTML version

and `welcome_email.text.erb` for the plain text version.

To change the default mailer view for your action you do something like:

```
class UserMailer < ApplicationMailer
  default from: 'notifications@example.com'
```