```
  def welcome_email(user)
    @user = user
    @url = 'http://example.com/login'
    mail(to: @user.email,
         subject: 'Welcome to My Awesome Site',
         template_path: 'notifications',
         template_name: 'another')
  end
end
```

In this case it will look for templates at `app/views/notifications` with name `another`. You can also specify an array of paths for `template_path`, and they will be searched in order.

If you want more flexibility you can also pass a block and render specific templates or even render inline or text without using a template file:

```
class UserMailer < ApplicationMailer
  default from: 'notifications@example.com'

  def welcome_email(user)
    @user = user
    @url = 'http://example.com/login'
    mail(to: @user.email,
         subject: 'Welcome to My Awesome Site') do |format|
      format.html { render 'another_template' }
      format.text { render text: 'Render text' }
    end
  end
end
```

This will render the template 'another_template.html.erb' for the HTML part and use the rendered text for the text part. The render command is the same one used inside of Action Controller, so you can use all the same options, such as `:text`, `:inline` etc.

2.5 Action Mailer Layouts

Just like controller views, you can also have mailer layouts. The layout name needs to be the same as your mailer, such as `user_mailer.html.erb` and `user_mailer.text.erb` to be automatically recognized by your mailer as a layout.

In order to use a different file, call `layout` in your mailer:

```
class UserMailer < ApplicationMailer
  layout 'awesome' # use awesome.(html|text).erb as the layout
end
```

Just like with controller views, use `yield` to render the view inside the layout.

You can also pass in a `layout: 'layout_name'` option to the render call inside the format block to specify different layouts for different formats:

```
class UserMailer < ApplicationMailer
  def welcome_email(user)
    mail(to: user.email) do |format|
      format.html { render layout: 'my_layout' }
      format.text
    end
  end
end
```

Will render the HTML part using the `my_layout.html.erb` file and the text part with the usual `user_mailer.text.erb` file if it exists.

2.6 Previewing Emails