Action Mailer previews provide a way to see how emails look by visiting a special URL that renders them. In the above example, the preview class for `UserMailer` should be named `UserMailerPreview` and located in `test/mailers/previews/user_mailer_preview.rb`. To see the preview of `welcome_email`, implement a method that has the same name and call `UserMailer.welcome_email`:

```
class UserMailerPreview < ActionMailer::Preview
  def welcome_email
    UserMailer.welcome_email(User.first)
  end
end
```

Then the preview will be available in http://localhost:3000/rails/mailers/user_mailer/welcome_email.

If you change something in `app/views/user_mailer/welcome_email.html.erb` or the mailer itself, it'll automatically reload and render it so you can visually see the new style instantly. A list of previews are also available in http://localhost:3000/rails/mailers.

By default, these preview classes live in `test/mailers/previews`. This can be configured using the `preview_path` option. For example, if you want to change it to `lib/mailer_previews`, you can configure it in `config/application.rb`:

```
config.action_mailer.preview_path =
"#{Rails.root}/lib/mailer_previews"
```

2.7 Generating URLs in Action Mailer Views

Unlike controllers, the mailer instance doesn't have any context about the incoming request so you'll need to provide the `:host` parameter yourself.

As the `:host` usually is consistent across the application you can configure it globally in `config/application.rb`:

```
config.action_mailer.default_url_options = { host: 'example.com' }
```

Because of this behavior you cannot use any of the `*_path` helpers inside of an email. Instead you will need to use the associated `*_url` helper. For example instead of using

```
<%= link_to 'welcome', welcome_path %>
```

You will need to use:

```
<%= link_to 'welcome', welcome_url %>
```

By using the full URL, your links will now work in your emails.

2.7.1 generating URLs with `url_for`

`url_for` generate full URL by default in templates.

If you did not configure the `:host` option globally make sure to pass it to `url_for`.

```
<%= url_for(host: 'example.com',
            controller: 'welcome',
            action: 'greeting') %>
```

2.7.2 generating URLs with named routes

Email clients have no web context and so paths have no base URL to form complete web addresses. Thus, you should always use the "_url" variant of named route helpers.

If you did not configure the `:host` option globally make sure to pass it to the url helper.

```
<%= user_url(@user, host: 'example.com') %>
```

2.8 Sending Multipart Emails

Action Mailer will automatically send multipart emails if you have different templates for the same action. So, for our UserMailer example, if you