Action Mailer now just inherits from `AbstractController`, so you have access to the same generic helpers as you do in Action Controller.

6 Action Mailer Configuration

The following configuration options are best made in one of the environment files (environment.rb, production.rb, etc...)

Configuration	Description
`logger`	Generates information on the mailing run if available. Can be set to `nil` for no logging. Compatible with both Ruby's own `Logger` and `Log4r` loggers.
`smtp_settings`	Allows detailed configuration for `:smtp` delivery method: • `:address` - Allows you to use a remote mail server. Just change it from its default `"localhost"` setting. • `:port` - On the off chance that your mail server doesn't run on port 25, you can change it. • `:domain` - If you need to specify a HELO domain, you can do it here. • `:user_name` - If your mail server requires authentication, set the username in this setting. • `:password` - If your mail server requires authentication, set the password in this setting. • `:authentication` - If your mail server requires authentication, you need to specify the authentication type here. This is a symbol and one of `:plain`, `:login`, `:cram_md5`. • `:enable_starttls_auto` - Set this to `false` if there is a problem with your server certificate that you cannot resolve.
`sendmail_settings`	Allows you to override options for the `:sendmail` delivery method. • `:location` - The location of the sendmail executable. Defaults to `/usr/sbin/sendmail`. • `:arguments` - The command line arguments to be passed to sendmail. Defaults to `-i -t`.
`raise_delivery_errors`	Whether or not errors should be raised if the email fails to be delivered. This only works if the external email server is configured for immediate delivery.
`delivery_method`	Defines a delivery method. Possible values are: • `:smtp` (default), can be configured by using `config.action_mailer.smtp_settings`. • `:sendmail`, can be configured by using `config.action_mailer.sendmail_settings`. • `:file`: save emails to files; can be configured by using `config.action_mailer.file_settings`.