Configuration	Description
	• `:test`: save emails to `ActionMailer::Base.deliveries`array. See API docs for more info.
`perform_deliveries`	Determines whether deliveries are actually carried out when the `deliver` method is invoked on the Mail message. By default they are, but this can be turned off to help functional testing.
`deliveries`	Keeps an array of all the emails sent out through the Action Mailer with delivery_method :test. Most useful for unit and functional testing.
`default_options`	Allows you to set default values for the `mail` method options (`:from`, `:reply_to`, etc.).

For a complete writeup of possible configurations see the Configuring Action Mailer in our Configuring Rails Applications guide.

6.1 Example Action Mailer Configuration

An example would be adding the following to your appropriate `config/environments/$RAILS_ENV.rb` file:

```
config.action_mailer.delivery_method = :sendmail
# Defaults to:
# config.action_mailer.sendmail_settings = {
#   location: '/usr/sbin/sendmail',
#   arguments: '-i -t'
# }
config.action_mailer.perform_deliveries = true
config.action_mailer.raise_delivery_errors = true
config.action_mailer.default_options = {from: 'no-reply@example.com'}
```

6.2 Action Mailer Configuration for Gmail

As Action Mailer now uses the Mail gem, this becomes as simple as adding to your `config/environments/$RAILS_ENV.rb` file:

```
config.action_mailer.delivery_method = :smtp
config.action_mailer.smtp_settings = {
  address:              'smtp.gmail.com',
  port:                 587,
  domain:               'example.com',
  user_name:            '<username>',
  password:             '<password>',
  authentication:       'plain',
  enable_starttls_auto: true }
```

7 Mailer Testing

You can find detailed instructions on how to test your mailers in the testing guide.

8 Intercepting Emails

There are situations where you need to edit an email before it's delivered. Fortunately Action Mailer provides hooks to intercept every email. You can register an interceptor to make modifications to mail messages right before they are handed to the delivery agents.