JSON	Parameters
`{ "person": [null] }`	`{ :person => [] }`
`{ "person": [null, null, ...] }`	`{ :person => [] }`
`{ "person": ["foo", null] }`	`{ :person => ["foo"] }`

It is possible to return to old behaviour and disable `deep_munge` configuring your application if you are aware of the risk and know how to handle it:

```
config.action_dispatch.perform_deep_munge = false
```

9 Default Headers

Every HTTP response from your Rails application receives the following default security headers.

```
config.action_dispatch.default_headers = {
  'X-Frame-Options' => 'SAMEORIGIN',
  'X-XSS-Protection' => '1; mode=block',
  'X-Content-Type-Options' => 'nosniff'
}
```

You can configure default headers in `config/application.rb`.

```
config.action_dispatch.default_headers = {
  'Header-Name' => 'Header-Value',
  'X-Frame-Options' => 'DENY'
}
```

Or you can remove them.

```
config.action_dispatch.default_headers.clear
```

Here is a list of common headers:

- X-Frame-Options *'SAMEORIGIN' in Rails by default* - allow framing on same domain. Set it to 'DENY' to deny framing at all or 'ALLOWALL' if you want to allow framing for all website.
- X-XSS-Protection *'1; mode=block' in Rails by default* - use XSS Auditor and block page if XSS attack is detected. Set it to '0;' if you want to switch XSS Auditor off(useful if response contents scripts from request parameters)
- X-Content-Type-Options *'nosniff' in Rails by default* - stops the browser from guessing the MIME type of a file.
- X-Content-Security-Policy A powerful mechanism for controlling which sites certain content types can be loaded from
- Access-Control-Allow-Origin Used to control which sites are allowed to bypass same origin policies and send cross-origin requests.
- Strict-Transport-Security Used to control if the browser is allowed to only access a site over a secure connection

10 Environmental Security

It is beyond the scope of this guide to inform you on how to secure your application code and environments. However, please secure your database configuration, e.g. `config/database.yml`, and your server-side secret, e.g. stored in `config/secrets.yml`. You may want to further restrict access, using environment-specific versions of these files and any others that may contain sensitive information.