```
=> Booting WEBrick
=> Rails 5.0.0 application starting in development on
http://0.0.0.0:3000
=> Run `rails server -h` for more startup options
=> Notice: server is listening on all interfaces (0.0.0.0). Consider
using 127.0.0.1 (--binding option)
=> Ctrl-C to shutdown server
[2014-04-11 13:11:47] INFO  WEBrick 1.3.1
[2014-04-11 13:11:47] INFO  ruby 2.1.1 (2014-02-24) [i686-linux]
[2014-04-11 13:11:47] INFO  WEBrick::HTTPServer#start: pid=6370
port=3000


Started GET "/" for 127.0.0.1 at 2014-04-11 13:11:48 +0200
  ActiveRecord::SchemaMigration Load (0.2ms)  SELECT
"schema_migrations".* FROM "schema_migrations"
Processing by ArticlesController#index as HTML

[3, 12] in /PathTo/project/app/controllers/articles_controller.rb
    3:
    4:   # GET /articles
    5:   # GET /articles.json
    6:   def index
    7:     byebug
=>  8:     @articles = Article.find_recent
    9:
   10:     respond_to do |format|
   11:       format.html # index.html.erb
   12:       format.json { render json: @articles }

(byebug)
```

Now it's time to explore and dig into your application. A good place to start is by asking the debugger for help. Type: `help`

```
(byebug) help

byebug 2.7.0

Type 'help <command-name>' for help on a specific command

Available commands:
backtrace  delete   enable  help       list    pry next  restart  source     up
break      disable  eval    info       method  ps        save     step       var
catch      display  exit    interrupt  next    putl      set      thread
condition  down     finish  irb        p       quit      show     trace
continue   edit     frame   kill       pp      reload    skip     undisplay
```

To view the help menu for any command use `help <command-name>` at the debugger prompt. For example: *`help list`*. You can abbreviate any debugging command by supplying just enough letters to distinguish them from other commands, so you can also use `l` for the `list` command, for example.

To see the previous ten lines you should type `list-` (or `l-`)

```
(byebug) l-

[1, 10] in /PathTo/project/app/controllers/articles_controller.rb
   1  class ArticlesController < ApplicationController
   2    before_action :set_article, only: [:show, :edit, :update,
:destroy]
   3
   4    # GET /articles
   5    # GET /articles.json
   6    def index
   7      byebug
   8      @articles = Article.find_recent
   9
```