```
   10      respond_to do |format|
```

This way you can move inside the file, being able to see the code above and over the line where you added the `byebug` call. Finally, to see where you are in the code again you can type `list=`

```
(byebug) list=

[3, 12] in /PathTo/project/app/controllers/articles_controller.rb
    3:
    4:   # GET /articles
    5:   # GET /articles.json
    6:   def index
    7:     byebug
=>  8:     @articles = Article.find_recent
    9:
   10:     respond_to do |format|
   11:       format.html # index.html.erb
   12:       format.json { render json: @articles }

(byebug)
```

4.3 The Context

When you start debugging your application, you will be placed in different contexts as you go through the different parts of the stack.

The debugger creates a context when a stopping point or an event is reached. The context has information about the suspended program which enables the debugger to inspect the frame stack, evaluate variables from the perspective of the debugged program, and contains information about the place where the debugged program is stopped.

At any time you can call the `backtrace` command (or its alias `where`) to print the backtrace of the application. This can be very helpful to know how you got where you are. If you ever wondered about how you got somewhere in your code, then `backtrace` will supply the answer.

```
(byebug) where
--> #0  ArticlesController.index
      at
/PathTo/project/test_app/app/controllers/articles_controller.rb:8
    #1  ActionController::ImplicitRender.send_action(method#String,
*args#Array)
      at /PathToGems/actionpack-
5.0.0/lib/action_controller/metal/implicit_render.rb:4
    #2  AbstractController::Base.process_action(action#NilClass,
*args#Array)
      at /PathToGems/actionpack-
5.0.0/lib/abstract_controller/base.rb:189
    #3  ActionController::Rendering.process_action(action#NilClass,
*args#NilClass)
      at /PathToGems/actionpack-
5.0.0/lib/action_controller/metal/rendering.rb:10
...
```

The current frame is marked with `-->`. You can move anywhere you want in this trace (thus changing the context) by using the `frame _n_` command, where *n* is the specified frame number. If you do that,`byebug` will display your new context.

```
(byebug) frame 2

[184, 193] in /PathToGems/actionpack-
5.0.0/lib/abstract_controller/base.rb
   184:       # is the intended way to override action dispatching.
   185:       #
```