```
   186:       # Notice that the first argument is the method to be
dispatched
   187:       # which is *not* necessarily the same as the action
name.
   188:       def process_action(method_name, *args)
=> 189:         send_action(method_name, *args)
   190:       end
   191:
   192:       # Actually call the method associated with the action.
Override
   193:       # this method if you wish to change how action methods
are called,

(byebug)
```

The available variables are the same as if you were running the code line by line. After all, that's what debugging is.

You can also use `up [n]` (`u` for abbreviated) and `down [n]` commands in order to change the context*n* frames up or down the stack respectively. *n* defaults to one. Up in this case is towards higher-numbered stack frames, and down is towards lower-numbered stack frames.

4.4 Threads

The debugger can list, stop, resume and switch between running threads by using the `thread`command (or the abbreviated `th`). This command has a handful of options:

- `thread` shows the current thread.
- `thread list` is used to list all threads and their statuses. The plus + character and the number indicates the current thread of execution.
- `thread stop _n_` stop thread *n*.
- `thread resume _n_` resumes thread *n*.
- `thread switch _n_` switches the current thread context to *n*.

This command is very helpful, among other occasions, when you are debugging concurrent threads and need to verify that there are no race conditions in your code.

4.5 Inspecting Variables

Any expression can be evaluated in the current context. To evaluate an expression, just type it!

This example shows how you can print the instance variables defined within the current context:

```
[3, 12] in /PathTo/project/app/controllers/articles_controller.rb
    3:
    4:   # GET /articles
    5:   # GET /articles.json
    6:   def index
    7:     byebug
=>  8:     @articles = Article.find_recent
    9:
   10:     respond_to do |format|
   11:       format.html # index.html.erb
   12:       format.json { render json: @articles }

(byebug) instance_variables
[:@_action_has_layout, :@_routes, :@_headers, :@_status, :@_request,
 :@_response, :@_env, :@_prefixes, :@_lookup_context, :@_action_name,
 :@_response_body, :@marked_for_same_origin_verification, :@_config]
```