```
   53:
   54:   def weeks
=> 55:     ActiveSupport::Duration.new(self * 7.days, [[:days, self *
7]])
   56:   end
   57:   alias :week :weeks
   58:
   59:   def fortnights

(byebug)
```

This is one of the best ways to find bugs in your code, or perhaps in Ruby on Rails.

4.7 Breakpoints

A breakpoint makes your application stop whenever a certain point in the program is reached. The debugger shell is invoked in that line.

You can add breakpoints dynamically with the command `break` (or just `b`). There are 3 possible ways of adding breakpoints manually:

- `break line`: set breakpoint in the *line* in the current source file.
- `break file:line [if expression]`: set breakpoint in the *line* number inside the *file*. If an*expression* is given it must evaluated to *true* to fire up the debugger.
- `break class(.|\#)method [if expression]`: set breakpoint in *method* (. and # for class and instance method respectively) defined in *class*. The *expression* works the same way as with file:line.

For example, in the previous situation

```
[4, 13] in /PathTo/project/app/controllers/articles_controller.rb
    4:   # GET /articles
    5:   # GET /articles.json
    6:   def index
    7:     @articles = Article.find_recent
    8:
=>  9:     respond_to do |format|
   10:       format.html # index.html.erb
   11:       format.json { render json: @articles }
   12:     end
   13:   end

(byebug) break 11
Created breakpoint 1 at
/PathTo/project/app/controllers/articles_controller.rb:11
```

Use `info breakpoints _n_` or `info break _n_` to list breakpoints. If you supply a number, it lists that breakpoint. Otherwise it lists all breakpoints.

```
(byebug) info breakpoints
Num Enb What
1   y   at /PathTo/project/app/controllers/articles_controller.rb:11
```

To delete breakpoints: use the command `delete _n_` to remove the breakpoint number *n*. If no number is specified, it deletes all breakpoints that are currently active.

```
(byebug) delete 1
(byebug) info breakpoints
No breakpoints.
```

You can also enable or disable breakpoints:

- `enable breakpoints`: allow a *breakpoints* list or all of them if no list is specified, to stop your program. This is the default state when you create a breakpoint.