following `config.filter_parameters+=[:password]` in `config/initializers/filter_parameter_logging.rb`.

- `config.force_ssl` forces all requests to be under HTTPS protocol by using `ActionDispatch::SSL` middleware.
- `config.log_formatter` defines the formatter of the Rails logger. This option defaults to an instance of `ActiveSupport::Logger::SimpleFormatter` for all modes except production, where it defaults to `Logger::Formatter`.
- `config.log_level` defines the verbosity of the Rails logger. This option defaults to `:debug`for all environments. The available log levels are: :debug, :info, :warn, :error, :fatal, and :unknown.
- `config.log_tags` accepts a list of methods that the `request` object responds to. This makes it easy to tag log lines with debug information like subdomain and request id - both very helpful in debugging multi-user production applications.
- `config.logger` accepts a logger conforming to the interface of Log4r or the default Ruby `Logger` class. Defaults to an instance of `ActiveSupport::Logger`.
- `config.middleware` allows you to configure the application's middleware. This is covered in depth in the Configuring Middleware section below.
- `config.reload_classes_only_on_change` enables or disables reloading of classes only when tracked files change. By default tracks everything on autoload paths and is set to true. If `config.cache_classes` is true, this option is ignored.
- `secrets.secret_key_base` is used for specifying a key which allows sessions for the application to be verified against a known secure key to prevent tampering. Applications get `secrets.secret_key_base` initialized to a random key present in `config/secrets.yml`.
- `config.serve_static_files` configures Rails to serve static files. This option defaults to true, but in the production environment it is set to false because the server software (e.g. NGINX or Apache) used to run the application should serve static files instead. If you are running or testing your app in production mode using WEBrick (it is not recommended to use WEBrick in production) set the option to true. Otherwise, you won't be able to use page caching and request for files that exist under the public directory.
- `config.session_store` is usually set up in `config/initializers/session_store.rb`and specifies what class to use to store the session. Possible values are `:cookie_store`which is the default, `:mem_cache_store`, and `:disabled`. The last one tells Rails not to deal with sessions. Custom session stores can also be specified:
  ```
  config.session_store :my_custom_store
  ```
- This custom store must be defined as `ActionDispatch::Session::MyCustomStore`.
- `config.time_zone` sets the default time zone for the application and enables time zone awareness for Active Record.

3.2 Configuring Assets

- `config.assets.enabled` a flag that controls whether the asset pipeline is enabled. It is set to true by default.
- `config.assets.raise_runtime_errors` Set this flag to `true` to enable additional runtime error checking. Recommended in `config/environments/development.rb` to minimize unexpected behavior when deploying to `production`.
- `config.assets.compress` a flag that enables the compression of compiled assets. It is explicitly set to true in `config/environments/production.rb`.
- `config.assets.css_compressor` defines the CSS compressor to use. It is set by default by `sass-rails`. The unique alternative value at the moment is `:yui`, which uses the `yui-compressor` gem.