- `config.assets.js_compressor` defines the JavaScript compressor to use. Possible values are `:closure`, `:uglifier` and `:yui` which require the use of the `closure-compiler`, `uglifier` or `yui-compressor` gems respectively.
- `config.assets.paths` contains the paths which are used to look for assets. Appending paths to this configuration option will cause those paths to be used in the search for assets.
- `config.assets.precompile` allows you to specify additional assets (other than `application.css` and `application.js`) which are to be precompiled when `rake assets:precompile` is run.
- `config.assets.prefix` defines the prefix where assets are served from. Defaults to `/assets`.
- `config.assets.manifest` defines the full path to be used for the asset precompiler's manifest file. Defaults to a file named `manifest-<random>.json` in the `config.assets.prefix` directory within the public folder.
- `config.assets.digest` enables the use of MD5 fingerprints in asset names. Set to `true`by default in `production.rb` and `development.rb`.
- `config.assets.debug` disables the concatenation and compression of assets. Set to `true`by default in `development.rb`.
- `config.assets.cache_store` defines the cache store that Sprockets will use. The default is the Rails file store.
- `config.assets.version` is an option string that is used in MD5 hash generation. This can be changed to force all files to be recompiled.
- `config.assets.compile` is a boolean that can be used to turn on live Sprockets compilation in production.
- `config.assets.logger` accepts a logger conforming to the interface of Log4r or the default Ruby `Logger` class. Defaults to the same configured at `config.logger`.
  Setting `config.assets.logger` to false will turn off served assets logging.

3.3 Configuring Generators

Rails allows you to alter what generators are used with the `config.generators` method. This method takes a block:

```
config.generators do |g|
  g.orm :active_record
  g.test_framework :test_unit
end
```

The full set of methods that can be used in this block are as follows:

- `assets` allows to create assets on generating a scaffold. Defaults to `true`.
- `force_plural` allows pluralized model names. Defaults to `false`.
- `helper` defines whether or not to generate helpers. Defaults to `true`.
- `integration_tool` defines which integration tool to use. Defaults to `nil`.
- `javascripts` turns on the hook for JavaScript files in generators. Used in Rails for when the`scaffold` generator is run. Defaults to `true`.
- `javascript_engine` configures the engine to be used (for eg. coffee) when generating assets. Defaults to `nil`.
- `orm` defines which orm to use. Defaults to `false` and will use Active Record by default.
- `resource_controller` defines which generator to use for generating a controller when using `rails generate resource`. Defaults to `:controller`.