- `config.active_record.primary_key_prefix_type` lets you adjust the naming for primary key columns. By default, Rails assumes that primary key columns are named `id`(and this configuration option doesn't need to be set.) There are two other choices: ** `:table_name` would make the primary key for the Customer class `customerid` ** `:table_name_with_underscore` would make the primary key for the Customer class `customer_id`
- `config.active_record.table_name_prefix` lets you set a global string to be prepended to table names. If you set this to `northwest_`, then the Customer class will look for `northwest_customers` as its table. The default is an empty string.
- `config.active_record.table_name_suffix` lets you set a global string to be appended to table names. If you set this to `_northwest`, then the Customer class will look for `customers_northwest` as its table. The default is an empty string.
- `config.active_record.schema_migrations_table_name` lets you set a string to be used as the name of the schema migrations table.
- `config.active_record.pluralize_table_names` specifies whether Rails will look for singular or plural table names in the database. If set to true (the default), then the Customer class will use the `customers` table. If set to false, then the Customer class will use the `customer` table.
- `config.active_record.default_timezone` determines whether to use `Time.local` (if set to `:local`) or `Time.utc` (if set to `:utc`) when pulling dates and times from the database. The default is `:utc`.
- `config.active_record.schema_format` controls the format for dumping the database schema to a file. The options are `:ruby` (the default) for a database-independent version that depends on migrations, or `:sql` for a set of (potentially database-dependent) SQL statements.
- `config.active_record.timestamped_migrations` controls whether migrations are numbered with serial integers or with timestamps. The default is true, to use timestamps, which are preferred if there are multiple developers working on the same application.
- `config.active_record.lock_optimistically` controls whether Active Record will use optimistic locking and is true by default.
- `config.active_record.cache_timestamp_format` controls the format of the timestamp value in the cache key. Default is `:number`.
- `config.active_record.record_timestamps` is a boolean value which controls whether or not timestamping of `create` and `update` operations on a model occur. The default value is `true`.
- `config.active_record.partial_writes` is a boolean value and controls whether or not partial writes are used (i.e. whether updates only set attributes that are dirty). Note that when using partial writes, you should also use optimistic locking `config.active_record.lock_optimistically` since concurrent updates may write attributes based on a possibly stale read state. The default value is `true`.
- `config.active_record.maintain_test_schema` is a boolean value which controls whether Active Record should try to keep your test database schema up-to-date with `db/schema.rb` (or `db/structure.sql`) when you run your tests. The default is true.
- `config.active_record.dump_schema_after_migration` is a flag which controls whether or not schema dump should happen (`db/schema.rb` or `db/structure.sql`) when you run migrations. This is set to false in `config/environments/production.rb` which is generated by Rails. The default value is true if this configuration is not set.
- `config.active_record.belongs_to_required_by_default` is a boolean value and controls whether `belongs_to` association is required by default.

The MySQL adapter adds one additional configuration option: