- `ActiveRecord::ConnectionAdapters::MysqlAdapter.emulate_booleans` controls whether Active Record will consider all `tinyint(1)` columns in a MySQL database to be booleans and is true by default.

The schema dumper adds one additional configuration option:

- `ActiveRecord::SchemaDumper.ignore_tables` accepts an array of tables that should *not*be included in any generated schema file. This setting is ignored unless `config.active_record.schema_format == :ruby`.

3.7 Configuring Action Controller

`config.action_controller` includes a number of configuration settings:

- `config.action_controller.asset_host` sets the host for the assets. Useful when CDNs are used for hosting assets rather than the application server itself.
- `config.action_controller.perform_caching` configures whether the application should perform caching or not. Set to false in development mode, true in production.
- `config.action_controller.default_static_extension` configures the extension used for cached pages. Defaults to `.html`.
- `config.action_controller.default_charset` specifies the default character set for all renders. The default is "utf-8".
- `config.action_controller.include_all_helpers` configures whether all view helpers are available everywhere or are scoped to the corresponding controller. If set to `false`, `UsersHelper` methods are only available for views rendered as part of `UsersController`. If`true`, `UsersHelper` methods are available everywhere. The default is `true`.
- `config.action_controller.logger` accepts a logger conforming to the interface of Log4r or the default Ruby Logger class, which is then used to log information from Action Controller. Set to `nil` to disable logging.
- `config.action_controller.request_forgery_protection_token` sets the token parameter name for RequestForgery. Calling `protect_from_forgery` sets it to `:authenticity_token` by default.
- `config.action_controller.allow_forgery_protection` enables or disables CSRF protection. By default this is `false` in test mode and `true` in all other modes.
- `config.action_controller.relative_url_root` can be used to tell Rails that you aredeploying to a subdirectory. The default is `ENV['RAILS_RELATIVE_URL_ROOT']`.
- `config.action_controller.permit_all_parameters` sets all the parameters for mass assignment to be permitted by default. The default value is `false`.
- `config.action_controller.action_on_unpermitted_parameters` enables logging or raising an exception if parameters that are not explicitly permitted are found. Set to `:log` or `:raise` to enable. The default value is `:log` in development and test environments, and `false` in all other environments.
- `config.action_controller.always_permitted_parameters` sets a list of whitelisted parameters that are permitted by default. The default values are `['controller', 'action']`.

3.8 Configuring Action Dispatch