- `config.action_dispatch.session_store` sets the name of the store for session data. The default is `:cookie_store`; other valid options include `:active_record_store`, `:mem_cache_store` or the name of your own custom class.
- `config.action_dispatch.default_headers` is a hash with HTTP headers that are set by default in each response. By default, this is defined as:

```
config.action_dispatch.default_headers = {
  'X-Frame-Options' => 'SAMEORIGIN',
  'X-XSS-Protection' => '1; mode=block',
  'X-Content-Type-Options' => 'nosniff'
}
```

- `config.action_dispatch.tld_length` sets the TLD (top-level domain) length for the application. Defaults to `1`.
- `config.action_dispatch.http_auth_salt` sets the HTTP Auth salt value. Defaults to `'http authentication'`.
- `config.action_dispatch.signed_cookie_salt` sets the signed cookies salt value. Defaults to `'signed cookie'`.
- `config.action_dispatch.encrypted_cookie_salt` sets the encrypted cookies salt value. Defaults to `'encrypted cookie'`.
- `config.action_dispatch.encrypted_signed_cookie_salt` sets the signed encrypted cookies salt value. Defaults to `'signed encrypted cookie'`.
- `config.action_dispatch.perform_deep_munge` configures whether `deep_munge` method should be performed on the parameters. See Security Guide for more information. It defaults to true.
- `config.action_dispatch.rescue_responses` configures what exceptions are assigned to an HTTP status. It accepts a hash and you can specify pairs of exception/status. By default, this is defined as:

```
config.action_dispatch.rescue_responses = {
  'ActionController::RoutingError'       => :not_found,
  'AbstractController::ActionNotFound'     => :not_found,
  'ActionController::MethodNotAllowed'     => :method_not_allowed,
  'ActionController::UnknownHttpMethod'     => :method_not_allowed,
  'ActionController::NotImplemented'      => :not_implemented,
  'ActionController::UnknownFormat'       => :not_acceptable,
  'ActionController::InvalidAuthenticityToken' =>
:unprocessable_entity,
  'ActionController::InvalidCrossOriginRequest' =>
:unprocessable_entity,
  'ActionDispatch::ParamsParser::ParseError'  => :bad_request,
  'ActionController::BadRequest'        => :bad_request,
  'ActionController::ParameterMissing'     => :bad_request,
  'ActiveRecord::RecordNotFound'        => :not_found,
  'ActiveRecord::StaleObjectError'       => :conflict,
  'ActiveRecord::RecordInvalid'         => :unprocessable_entity,
  'ActiveRecord::RecordNotSaved'        => :unprocessable_entity
}
```

Any exceptions that are not configured will be mapped to 500 Internal Server Error.

- `ActionDispatch::Callbacks.before` takes a block of code to run before the request.
- `ActionDispatch::Callbacks.to_prepare` takes a block to run after `ActionDispatch::Callbacks.before`, but before the request. Runs for every request in `development` mode, but only once for `production` or environments with `cache_classes`set to `true`.