- `ActionDispatch::Callbacks.after` takes a block of code to run after the request.

3.9 Configuring Action View

`config.action_view` includes a small number of configuration settings:

- `config.action_view.field_error_proc` provides an HTML generator for displaying errors that come from Active Record. The default is
```
Proc.new do |html_tag, instance|
  %Q(<div
class="field_with_errors">#{html_tag}</div>).html_safe
end
```
- `config.action_view.default_form_builder` tells Rails which form builder to use by default. The default is `ActionView::Helpers::FormBuilder`. If you want your form builder class to be loaded after initialization (so it's reloaded on each request in development), you can pass it as a `String`
- `config.action_view.logger` accepts a logger conforming to the interface of Log4r or the default Ruby Logger class, which is then used to log information from Action View. Set to `nil` to disable logging.
- `config.action_view.erb_trim_mode` gives the trim mode to be used by ERB. It defaults to `'-'`, which turns on trimming of tail spaces and newline when using `<%= -%>` or `<%= =%>`. See the Erubis documentation for more information.
- `config.action_view.embed_authenticity_token_in_remote_forms` allows you to set the default behavior for `authenticity_token` in forms with `:remote => true`. By default it's set to false, which means that remote forms will not include `authenticity_token`, which is helpful when you're fragment-caching the form. Remote forms get the authenticity from the`meta` tag, so embedding is unnecessary unless you support browsers without JavaScript. In such case you can either pass `:authenticity_token => true` as a form option or set this config setting to `true`
- `config.action_view.prefix_partial_path_with_controller_namespace` determines whether or not partials are looked up from a subdirectory in templates rendered from namespaced controllers. For example, consider a controller named `Admin::ArticlesController` which renders this template:
```
<%= render @article %>
```
- The default setting is `true`, which uses the partial at `/admin/articles/_article.erb`. Setting the value to `false` would render `/articles/_article.erb`, which is the same behavior as rendering from a non-namespaced controller such as `ArticlesController`.
- `config.action_view.raise_on_missing_translations` determines whether an error should be raised for missing translations

3.10 Configuring Action Mailer

There are a number of settings available on `config.action_mailer`:

- `config.action_mailer.logger` accepts a logger conforming to the interface of Log4r or the default Ruby Logger class, which is then used to log information from Action Mailer. Set to `nil` to disable logging.
- `config.action_mailer.smtp_settings` allows detailed configuration for the `:smtp`delivery method. It accepts a hash of options, which can include any of these options:
  - `:address` - Allows you to use a remote mail server. Just change it from its default "localhost" setting.
  - `:port` - On the off chance that your mail server doesn't run on port 25, you can change it.
  - `:domain` - If you need to specify a HELO domain, you can do it here.