the `middleware` method, its middleware is inserted before `Rack::Runtime` in the middleware stack.

- `set_clear_dependencies_hook` Provides a hook for `active_record.set_dispatch_hooks` to use, which will run before this initializer. This initializer - which runs only if `cache_classes` is set to `false` - uses `ActionDispatch::Callbacks.after` to remove the constants which have been referenced during the request from the object space so that they will be reloaded during the following request.
- `initialize_dependency_mechanism` If `config.cache_classes` is true, configures `ActiveSupport::Dependencies.mechanism` to `require` dependencies rather than `load`them.
- `bootstrap_hook` Runs all configured `before_initialize` blocks.
- `i18n.callbacks` In the development environment, sets up a `to_prepare` callback which will call `I18n.reload!` if any of the locales have changed since the last request. In production mode this callback will only run on the first request.
- `active_support.deprecation_behavior` Sets up deprecation reporting for environments, defaulting to `:log` for development, `:notify` for production and `:stderr` for test. If a value isn't set for `config.active_support.deprecation` then this initializer will prompt the user to configure this line in the current environment's `config/environments` file. Can be set to an array of values.
- `active_support.initialize_time_zone` Sets the default time zone for the application based on the `config.time_zone` setting, which defaults to "UTC".
- `active_support.initialize_beginning_of_week` Sets the default beginning of week for the application based on `config.beginning_of_week` setting, which defaults to `:monday`.
- `action_dispatch.configure` Configures the `ActionDispatch::Http::URL.tld_length`to be set to the value of `config.action_dispatch.tld_length`.
- `action_view.set_configs` Sets up Action View by using the settings in `config.action_view` by `send`'ing the method names as setters to `ActionView::Base` and passing the values through.
- `action_controller.logger` Sets `ActionController::Base.logger` - if it's not already set - to `Rails.logger`.
- `action_controller.initialize_framework_caches` Sets `ActionController::Base.cache_store` - if it's not already set - to `Rails.cache`.
- `action_controller.set_configs` Sets up Action Controller by using the settings in `config.action_controller` by `send`'ing the method names as setters to `ActionController::Base` and passing the values through.
- `action_controller.compile_config_methods` Initializes methods for the config settings specified so that they are quicker to access.
- `active_record.initialize_timezone` Sets `ActiveRecord::Base.time_zone_aware_attributes` to true, as well as setting `ActiveRecord::Base.default_timezone` to UTC. When attributes are read from the database, they will be converted into the time zone specified by `Time.zone`.
- `active_record.logger` Sets `ActiveRecord::Base.logger` - if it's not already set - to `Rails.logger`.
- `active_record.set_configs` Sets up Active Record by using the settings in `config.active_record` by `send`'ing the method names as setters to `ActiveRecord::Base`and passing the values through.
- `active_record.initialize_database` Loads the database configuration (by default) from`config/database.yml` and establishes a connection for the current environment.