- `active_record.log_runtime` Includes `ActiveRecord::Railties::ControllerRuntime`which is responsible for reporting the time taken by Active Record calls for the request back to the logger.
- `active_record.set_dispatch_hooks` Resets all reloadable connections to the database if`config.cache_classes` is set to `false`.
- `action_mailer.logger` Sets `ActionMailer::Base.logger` - if it's not already set - to `Rails.logger`.
- `action_mailer.set_configs` Sets up Action Mailer by using the settings in `config.action_mailer` by `send`'ing the method names as setters to `ActionMailer::Base`and passing the values through.
- `action_mailer.compile_config_methods` Initializes methods for the config settings specified so that they are quicker to access.
- `set_load_path` This initializer runs before `bootstrap_hook`. Adds the `vendor`, `lib`, all directories of `app` and any paths specified by `config.load_paths` to `$LOAD_PATH`.
- `set_autoload_paths` This initializer runs before `bootstrap_hook`. Adds all sub-directories of `app` and paths specified by `config.autoload_paths` to `ActiveSupport::Dependencies.autoload_paths`.
- `add_routing_paths` Loads (by default) all `config/routes.rb` files (in the application and railties, including engines) and sets up the routes for the application.
- `add_locales` Adds the files in `config/locales` (from the application, railties and engines) to `I18n.load_path`, making available the translations in these files.
- `add_view_paths` Adds the directory `app/views` from the application, railties and engines to the lookup path for view files for the application.
- `load_environment_config` Loads the `config/environments` file for the current environment.
- `append_asset_paths` Finds asset paths for the application and all attached railties and keeps a track of the available directories in `config.static_asset_paths`.
- `prepend_helpers_path` Adds the directory `app/helpers` from the application, railties and engines to the lookup path for helpers for the application.
- `load_config_initializers` Loads all Ruby files from `config/initializers` in the application, railties and engines. The files in this directory can be used to hold configuration settings that should be made after all of the frameworks are loaded.
- `engines_blank_point` Provides a point-in-initialization to hook into if you wish to do anything before engines are loaded. After this point, all railtie and engine initializers are run.
- `add_generator_templates` Finds templates for generators at `lib/templates` for the application, railties and engines and adds these to the `config.generators.templates`setting, which will make the templates available for all generators to reference.
- `ensure_autoload_once_paths_as_subset` Ensures that the `config.autoload_once_paths` only contains paths from `config.autoload_paths`. If it contains extra paths, then an exception will be raised.
- `add_to_prepare_blocks` The block for every `config.to_prepare` call in the application, a railtie or engine is added to the `to_prepare` callbacks for Action Dispatch which will be run per request in development, or before the first request in production.
- `add_builtin_route` If the application is running under the development environment then this will append the route for `rails/info/properties` to the application routes. This route provides the detailed information such as Rails and Ruby version for `public/index.html` in a default Rails application.
- `build_middleware_stack` Builds the middleware stack for the application, returning an object which has a `call` method which takes a Rack environment object for the request.