## 1.7 rails destroy

Think of `destroy` as the opposite of `generate`. It'll figure out what generate did, and undo it.
You can also use the alias "d" to invoke the destroy command: `rails d`.

```
$ bin/rails generate model Oops
      invoke  active_record
      create    db/migrate/20120528062523_create_oops.rb
      create    app/models/oops.rb
      invoke    test_unit
      create      test/models/oops_test.rb
      create      test/fixtures/oops.yml
$ bin/rails destroy model Oops
      invoke  active_record
      remove    db/migrate/20120528062523_create_oops.rb
      remove    app/models/oops.rb
      invoke    test_unit
      remove      test/models/oops_test.rb
      remove      test/fixtures/oops.yml
```

# 2 Rake

Rake is Ruby Make, a standalone Ruby utility that replaces the Unix utility 'make', and uses a 'Rakefile' and `.rake` files to build up a list of tasks. In Rails, Rake is used for common administration tasks, especially sophisticated ones that build off of each other.
You can get a list of Rake tasks available to you, which will often depend on your current directory, by typing `rake --tasks`. Each task has a description, and should help you find the thing you need.
To get the full backtrace for running rake task you can pass the option `--trace` to command line, for example `rake db:create --trace`.

```
$ bin/rake --tasks
rake about              # List versions of all Rails frameworks and
the environment
rake assets:clean       # Remove old compiled assets
rake assets:clobber     # Remove compiled assets
rake assets:precompile  # Compile all the assets named in
config.assets.precompile
rake db:create          # Create the database from config/database.yml
for the current Rails.env
...
rake log:clear          # Truncates all *.log files in log/ to zero
bytes (specify which logs with LOGS=test,development)
rake middleware         # Prints out your Rack middleware stack
...
rake tmp:clear          # Clear cache and socket files from tmp/
(narrow w/ tmp:cache:clear, tmp:sockets:clear)
rake tmp:create         # Creates tmp directories for cache, sockets,
and pids
```

You can also use `rake -T` to get the list of tasks.

## 2.1 about

`rake about` gives information about version numbers for Ruby, RubyGems, Rails, the Rails subcomponents, your application's folder, the current Rails environment name, your app's database adapter, and schema version. It is useful when you need to ask for help, check if a security patch might affect you, or when you need some stats for an existing Rails installation.

```
$ bin/rake about
About your application's environment
Rails version             5.0.0
Ruby version              2.2.0 (x86_64-linux)
RubyGems version          2.4.5
Rack version              1.6
JavaScript Runtime        Node.js (V8)
```