When using specific annotations and custom annotations, the annotation name (FIXME, BUG etc) is not displayed in the output lines.

By default, `rake notes` will look in the `app`, `config`, `lib`, `bin` and `test` directories. If you would like to search other directories, you can provide them as a comma separated list in an environment variable `SOURCE_ANNOTATION_DIRECTORIES`.

```
$ export SOURCE_ANNOTATION_DIRECTORIES='spec,vendor'
$ bin/rake notes
(in /home/foobar/commandsapp)
app/models/user.rb:
  * [ 35] [FIXME] User should have a subscription at this point
spec/models/user_spec.rb:
  * [122] [TODO] Verify the user that has a subscription works
```

2.5 `routes`

`rake routes` will list all of your defined routes, which is useful for tracking down routing problems in your app, or giving you a good overview of the URLs in an app you're trying to get familiar with.

2.6 `test`

A good description of unit testing in Rails is given in A Guide to Testing Rails Applications

Rails comes with a test suite called Minitest. Rails owes its stability to the use of tests. The tasks available in the `test:` namespace helps in running the different tests you will hopefully write.

2.7 `tmp`

The `Rails.root/tmp` directory is, like the *nix /tmp directory, the holding place for temporary files like process id files and cached actions.

The `tmp:` namespaced tasks will help you clear and create the `Rails.root/tmp` directory:

- `rake tmp:cache:clear` clears `tmp/cache`.
- `rake tmp:sockets:clear` clears `tmp/sockets`.
- `rake tmp:clear` clears all cache and sockets files.
- `rake tmp:create` creates tmp directories for cache, sockets and pids.

2.8 Miscellaneous

- `rake stats` is great for looking at statistics on your code, displaying things like KLOCs (thousands of lines of code) and your code to test ratio.
- `rake secret` will give you a pseudo-random key to use for your session secret.
- `rake time:zones:all` lists all the timezones Rails knows about.

2.9 Custom Rake Tasks

Custom rake tasks have a `.rake` extension and are placed in `Rails.root/lib/tasks`. You can create these custom rake tasks with the `bin/rails generate task` command.

```
desc "I am short, but comprehensive description for my cool task"
task task_name: [:prerequisite_task, :another_task_we_depend_on] do
  # All your magic here
  # Any valid Ruby code is allowed
end
```

To pass arguments to your custom rake task:

```
task :task_name, [:arg_1] => [:pre_1, :pre_2] do |t, args|
  # You can use args from here
end
```

You can group tasks by placing them in namespaces: