```
namespace :db do
  desc "This task does nothing"
  task :nothing do
    # Seriously, nothing
  end
end
```

Invocation of the tasks will look like:

```
$ bin/rake task_name
$ bin/rake "task_name[value 1]" # entire argument string should be
quoted
$ bin/rake db:nothing
```

If your need to interact with your application models, perform database queries and so on, your task should depend on the `environment` task, which will load your application code.

# 3 The Rails Advanced Command Line

More advanced use of the command line is focused around finding useful (even surprising at times) options in the utilities, and fitting those to your needs and specific work flow. Listed here are some tricks up Rails' sleeve.

## 3.1 Rails with Databases and SCM

When creating a new Rails application, you have the option to specify what kind of database and what kind of source code management system your application is going to use. This will save you a few minutes, and certainly many keystrokes.

Let's see what a `--git` option and a `--database=postgresql` option will do for us:

```
$ mkdir gitapp
$ cd gitapp
$ git init
Initialized empty Git repository in .git/
$ rails new . --git --database=postgresql
      exists
      create  app/controllers
      create  app/helpers
...
...
      create  tmp/cache
      create  tmp/pids
      create  Rakefile
add 'Rakefile'
      create  README.rdoc
add 'README.rdoc'
      create  app/controllers/application_controller.rb
add 'app/controllers/application_controller.rb'
      create  app/helpers/application_helper.rb
...
      create  log/test.log
add 'log/test.log'
```

We had to create the **gitapp** directory and initialize an empty git repository before Rails would add files it created to our repository. Let's see what it put in our database configuration:

```
$ cat config/database.yml
# PostgreSQL. Versions 8.2 and up are supported.
#
# Install the pg driver:
#   gem install pg
# On OS X with Homebrew:
#   gem install pg -- --with-pg-config=/usr/local/bin/pg_config
# On OS X with MacPorts:
```