browser as JavaScript and CSS respectively. When asset pipelining is enabled, these files are preprocessed and placed in the `public/assets` directory for serving by either the Rails app or web server.
Additional layers of preprocessing can be requested by adding other extensions, where each extension is processed in a right-to-left manner. These should be used in the order the processing should be applied. For example, a stylesheet called `app/assets/stylesheets/projects.scss.erb` is first processed as ERB, then SCSS, and finally served as CSS. The same applies to a JavaScript file
- `app/assets/javascripts/projects.coffee.erb` is processed as ERB, then CoffeeScript, and served as JavaScript.
Keep in mind the order of these preprocessors is important. For example, if you called your JavaScript file `app/assets/javascripts/projects.erb.coffee` then it would be processed with the CoffeeScript interpreter first, which wouldn't understand ERB and therefore you would run into problems.

3 In Development

In development mode, assets are served as separate files in the order they are specified in the manifest file.

This manifest `app/assets/javascripts/application.js`:

```
//= require core
//= require projects
//= require tickets
```

would generate this HTML:

```
<script src="/assets/core.js?body=1"></script>
<script src="/assets/projects.js?body=1"></script>
<script src="/assets/tickets.js?body=1"></script>
```

The `body` param is required by Sprockets.

3.1 Runtime Error Checking

By default the asset pipeline will check for potential errors in development mode during runtime. To disable this behavior you can set:

```
config.assets.raise_runtime_errors = false
```

When this option is true, the asset pipeline will check if all the assets loaded in your application are included in the `config.assets.precompile` list. If `config.assets.digest` is also true, the asset pipeline will require that all requests for assets include digests.

3.2 Turning Digests Off

You can turn off digests by updating `config/environments/development.rb` to include:

```
config.assets.digest = false
```

When this option is true, digests will be generated for asset URLs.

3.3 Turning Debugging Off

You can turn off debug mode by updating `config/environments/development.rb` to include:

```
config.assets.debug = false
```

When debug mode is off, Sprockets concatenates and runs the necessary preprocessors on all files. With debug mode turned off the manifest above would generate instead: