5.3 Using Your Own Compressor

The compressor config settings for CSS and JavaScript also take any object. This object must have a`compress` method that takes a string as the sole argument and it must return a string.

```
class Transformer
  def compress(string)
    do_something_returning_a_string(string)
  end
end
```

To enable this, pass a new object to the config option in `application.rb`:

```
config.assets.css_compressor = Transformer.new
```

5.4 Changing the *assets* Path

The public path that Sprockets uses by default is `/assets`.

This can be changed to something else:

```
config.assets.prefix = "/some_other_path"
```

This is a handy option if you are updating an older project that didn't use the asset pipeline and already uses this path or you wish to use this path for a new resource.

5.5 X-Sendfile Headers

The X-Sendfile header is a directive to the web server to ignore the response from the application, and instead serve a specified file from disk. This option is off by default, but can be enabled if your server supports it. When enabled, this passes responsibility for serving the file to the web server, which is faster. Have a look at send_file on how to use this feature.

Apache and NGINX support this option, which can be enabled in `config/environments/production.rb`:

```
# config.action_dispatch.x_sendfile_header = "X-Sendfile" # for Apache
# config.action_dispatch.x_sendfile_header = 'X-Accel-Redirect' # for
NGINX
```

If you are upgrading an existing application and intend to use this option, take care to paste this configuration option only into `production.rb` and any other environments you define with production behavior (not `application.rb`).

For further details have a look at the docs of your production web server: - Apache - NGINX

6 Assets Cache Store

The default Rails cache store will be used by Sprockets to cache assets in development and production.

This can be changed by setting `config.assets.cache_store`:

```
config.assets.cache_store = :memory_store
```

The options accepted by the assets cache store are the same as the application's cache store.

```
config.assets.cache_store = :memory_store, { size: 32.megabytes }
```

To disable the assets cache store:

```
config.assets.configure do |env|
  env.cache = ActiveSupport::Cache.lookup_store(:null_store)
end
```

7 Adding Assets to Your Gems

Assets can also come from external sources in the form of gems.