```
<form accept-charset="UTF-8" action="/articles" data-remote="true"
method="post">
  ...
</form>
```

Everything else is the same as `form_for`. See its documentation for full details.

3.3 link_to

`link_to` is a helper that assists with generating links. It has a `:remote` option you can use like this:

```
<%= link_to "an article", @article, remote: true %>
```

which generates

```
<a href="/articles/1" data-remote="true">an article</a>
```

You can bind to the same Ajax events as `form_for`. Here's an example. Let's assume that we have a list of articles that can be deleted with just one click. We would generate some HTML like this:

```
<%= link_to "Delete article", @article, remote: true, method: :delete
%>
```

and write some CoffeeScript like this:

```
$ ->
  $("a[data-remote]").on "ajax:success", (e, data, status, xhr) ->
    alert "The article was deleted."
```

3.4 button_to

`button_to` is a helper that helps you create buttons. It has a `:remote` option that you can call like this:

```
<%= button_to "An article", @article, remote: true %>
```

this generates

```
<form action="/articles/1" class="button_to" data-remote="true"
method="post">
  <div><input type="submit" value="An article"></div>
</form>
```

Since it's just a `<form>`, all of the information on `form_for` also applies.

4 Server-Side Concerns

Ajax isn't just client-side, you also need to do some work on the server side to support it. Often, people like their Ajax requests to return JSON rather than HTML. Let's discuss what it takes to make that happen.

4.1 A Simple Example

Imagine you have a series of users that you would like to display and provide a form on that same page to create a new user. The index action of your controller looks like this:

```
class UsersController < ApplicationController
  def index
    @users = User.all
    @user = User.new
  end
  # ...
```

The index view (`app/views/users/index.html.erb`) contains:

```
<b>Users</b>

<ul id="users">
<%= render @users %>
```