```
</ul>

<br>

<%= form_for(@user, remote: true) do |f| %>
  <%= f.label :name %><br>
  <%= f.text_field :name %>
  <%= f.submit %>
<% end %>
```

The `app/views/users/_user.html.erb` partial contains the following:

```
<li><%= user.name %></li>
```

The top portion of the index page displays the users. The bottom portion provides a form to create a new user.

The bottom form will call the `create` action on the `UsersController`. Because the form's remote option is set to true, the request will be posted to the `UsersController` as an Ajax request, looking for JavaScript. In order to serve that request, the `create` action of your controller would look like this:

```
# app/controllers/users_controller.rb
# ......
def create
  @user = User.new(params[:user])

  respond_to do |format|
    if @user.save
      format.html { redirect_to @user, notice: 'User was successfully
created.' }
      format.js   {}
      format.json { render json: @user, status: :created, location:
@user }
    else
      format.html { render action: "new" }
      format.json { render json: @user.errors, status:
:unprocessable_entity }
    end
  end
end
```

Notice the format.js in the `respond_to` block; that allows the controller to respond to your Ajax request. You then have a corresponding `app/views/users/create.js.erb` view file that generates the actual JavaScript code that will be sent and executed on the client side.

```
$("<%= escape_javascript(render @user) %>").appendTo("#users");
```

5 Turbolinks

Rails 4 ships with the Turbolinks gem. This gem uses Ajax to speed up page rendering in most applications.

5.1 How Turbolinks Works

Turbolinks attaches a click handler to all `<a>` on the page. If your browser supports PushState, Turbolinks will make an Ajax request for the page, parse the response, and replace the entire `<body>`of the page with the `<body>` of the response. It will then use PushState to change the URL to the correct one, preserving refresh semantics and giving you pretty URLs.

The only thing you have to do to enable Turbolinks is have it in your Gemfile, and put `//= require turbolinks` in your CoffeeScript manifest, which is usually `app/assets/javascripts/application.js`.

If you want to disable Turbolinks for certain links, add a `data-no-turbolink` attribute to the tag:

```
<a href="..." data-no-turbolink>No turbolinks here</a>.
```