```
gem "rspec", group: "test", version: "2.1.0"
gem "devise", "1.1.5"
```

Available options are:

- `:group` - The group in the `Gemfile` where this gem should go.
- `:version` - The version string of the gem you want to use. Can also be specified as the second argument to the method.
- `:git` - The URL to the git repository for this gem.

Any additional options passed to this method are put on the end of the line:

```
gem "devise", git: "git://github.com/plataformatec/devise", branch:
"master"
```

The above code will put the following line into `Gemfile`:

```
gem "devise", git: "git://github.com/plataformatec/devise", branch:
"master"
```

9.2 gem_group

Wraps gem entries inside a group:

```
gem_group :development, :test do
  gem "rspec-rails"
end
```

9.3 add_source

Adds a specified source to `Gemfile`:

```
add_source "http://gems.github.com"
```

9.4 inject_into_file

Injects a block of code into a defined position in your file.

```
inject_into_file 'name_of_file.rb', after: "#The code goes below this
line. Don't forget the Line break at the end\n" do <<-'RUBY'
  puts "Hello World"
RUBY
end
```

9.5 gsub_file

Replaces text inside a file.

```
gsub_file 'name_of_file.rb', 'method.to_be_replaced',
'method.the_replacing_code'
```

Regular Expressions can be used to make this method more precise. You can also use `append_file`and `prepend_file` in the same way to place code at the beginning and end of a file respectively.

9.6 application

Adds a line to `config/application.rb` directly after the application class definition.

```
application "config.asset_host = 'http://example.com'"
```

This method can also take a block:

```
application do
  "config.asset_host = 'http://example.com'"
end
```

Available options are:

- `:env` - Specify an environment for this configuration option. If you wish to use this option with the block syntax the recommended syntax is as follows: