```
application(nil, env: "development") do
  "config.asset_host = 'http://localhost:3000'"
end
```

9.7 git

Runs the specified git command:

```
git :init
git add: "."
git commit: "-m First commit!"
git add: "onefile.rb", rm: "badfile.cxx"
```

The values of the hash here being the arguments or options passed to the specific git command. As per the final example shown here, multiple git commands can be specified at a time, but the order of their running is not guaranteed to be the same as the order that they were specified in.

9.8 vendor

Places a file into `vendor` which contains the specified code.

```
vendor "sekrit.rb", '#top secret stuff'
```

This method also takes a block:

```
vendor "seeds.rb" do
  "puts 'in your app, seeding your database'"
end
```

9.9 lib

Places a file into `lib` which contains the specified code.

```
lib "special.rb", "p Rails.root"
```

This method also takes a block:

```
lib "super_special.rb" do
  puts "Super special!"
end
```

9.10 rakefile

Creates a Rake file in the `lib/tasks` directory of the application.

```
rakefile "test.rake", "hello there"
```

This method also takes a block:

```
rakefile "test.rake" do
  %Q{
    task rock: :environment do
      puts "Rockin'"
    end
  }
end
```

9.11 initializer

Creates an initializer in the `config/initializers` directory of the application:

```
initializer "begin.rb", "puts 'this is the beginning'"
```

This method also takes a block, expected to return a string:

```
initializer "begin.rb" do
  "puts 'this is the beginning'"
end
```

9.12 generate

Runs the specified generator where the first argument is the generator name and the remaining arguments are passed directly to the generator.