4.4 Running Specific Migrations

If you need to run a specific migration up or down, the `db:migrate:up` and `db:migrate:down` tasks will do that. Just specify the appropriate version and the corresponding migration will have its `change`,`up` or `down` method invoked, for example:

```
$ bin/rake db:migrate:up VERSION=20080906120000
```

will run the 20080906120000 migration by running the `change` method (or the `up` method). This task will first check whether the migration is already performed and will do nothing if Active Record believes that it has already been run.

4.5 Running Migrations in Different Environments

By default running `rake db:migrate` will run in the `development` environment. To run migrations against another environment you can specify it using the `RAILS_ENV` environment variable while running the command. For example to run migrations against the `test` environment you could run:

```
$ bin/rake db:migrate RAILS_ENV=test
```

4.6 Changing the Output of Running Migrations

By default migrations tell you exactly what they're doing and how long it took. A migration creating a table and adding an index might produce output like this

```
==  CreateProducts: migrating
=============================================
-- create_table(:products)
   -> 0.0028s
==  CreateProducts: migrated (0.0028s)
========================================
```

Several methods are provided in migrations that allow you to control all this:

Method	Purpose
suppress_messages	Takes a block as an argument and suppresses any output generated by the block.
say	Takes a message argument and outputs it as is. A second boolean argument can be passed to specify whether to indent or not.
say_with_time	Outputs text along with how long it took to run its block. If the block returns an integer it assumes it is the number of rows affected.

For example, this migration:

```
class CreateProducts < ActiveRecord::Migration
  def change
    suppress_messages do
      create_table :products do |t|
        t.string :name
        t.text :description
        t.timestamps null: false
      end
    end

    say "Created a table"
```