```
    suppress_messages {add_index :products, :name}
    say "and an index!", true

    say_with_time 'Waiting for a while' do
      sleep 10
      250
    end
  end
end
```

generates the following output

```
==  CreateProducts: migrating
=============================================
-- Created a table
   -> and an index!
-- Waiting for a while
   -> 10.0013s
   -> 250 rows
==  CreateProducts: migrated (10.0054s)
========================================
```

If you want Active Record to not output anything, then running `rake db:migrate VERBOSE=false` will suppress all output.

5 Changing Existing Migrations

Occasionally you will make a mistake when writing a migration. If you have already run the migration then you cannot just edit the migration and run the migration again: Rails thinks it has already run the migration and so will do nothing when you run `rake db:migrate`. You must rollback the migration (for example with `rake db:rollback`), edit your migration and then run `rake db:migrate` to run the corrected version. In general, editing existing migrations is not a good idea. You will be creating extra work for yourself and your co-workers and cause major headaches if the existing version of the migration has already been run on production machines. Instead, you should write a new migration that performs the changes you require. Editing a freshly generated migration that has not yet been committed to source control (or, more generally, which has not been propagated beyond your development machine) is relatively harmless.

The `revert` method can be helpful when writing a new migration to undo previous migrations in whole or in part (see Reverting Previous Migrations above).

6 Schema Dumping and You

6.1 What are Schema Files for?

Migrations, mighty as they may be, are not the authoritative source for your database schema. That role falls to either `db/schema.rb` or an SQL file which Active Record generates by examining the database. They are not designed to be edited, they just represent the current state of the database.
There is no need (and it is error prone) to deploy a new instance of an app by replaying the entire migration history. It is much simpler and faster to just load into the database a description of the current schema.

For example, this is how the test database is created: the current development database is dumped (either to `db/schema.rb` or `db/structure.sql`) and then loaded into the test database.