

This error indicates that Rails cannot find the `new` action inside the `ArticlesController` that you just generated. This is because when controllers are generated in Rails they are empty by default, unless you tell it your desired actions during the generation process.
To manually define an action inside a controller, all you need to do is to define a new method inside the controller. Open `app/controllers/articles_controller.rb` and inside the `ArticlesController` class, define the `new` method so that your controller now looks like this:

```
class ArticlesController < ApplicationController
  def new
  end
end
```

With the `new` method defined in `ArticlesController`, if you refreshhttp://localhost:3000/articles/new you'll see another error:



You're getting this error now because Rails expects plain actions like this one to have views associated with them to display their information. With no view available, Rails will raise an exception.

In the above image, the bottom line has been truncated. Let's see what the full error message looks like:

*Missing template articles/new, application/new with {locale:[:en], formats:[:html], handlers:[:erb, :builder, :coffee]}. Searched in: * "/path/to/blog/app/views"*

That's quite a lot of text! Let's quickly go through and understand what each part of it means.

The first part identifies which template is missing. In this case, it's the `articles/new` template. Rails will first look for this template. If not found, then it will attempt to load a template called `application/new`. It looks for one here because the `ArticlesController` inherits from `ApplicationController`.
The next part of the message contains a hash. The `:locale` key in this hash simply indicates which spoken language template should be retrieved. By default, this is the English - or "en" - template. The next key, `:formats` specifies the format of template to be served in response. The default format is `:html`, and so Rails is looking for an HTML template. The final key, `:handlers`, is telling us what *template handlers* could be used to render our template. `:erb` is most commonly used for HTML templates, `:builder` is used for XML templates, and `:coffee` uses CoffeeScript to build JavaScript templates.
The final part of this message tells us where Rails has looked for the templates. Templates within a basic Rails application like this are kept in a single location, but in more complex applications it could be many different paths.

The simplest template that would work in this case would be one located at `app/views/articles/new.html.erb`. The extension of this file name is important: the first extension is the *format* of the template, and the second extension is the *handler* that will be used. Rails is attempting to